
Feature Summary

24/48-Pin Printers.....F-3

9-Pin PrintersF-78

This section lists the features and options of all dot-matrix printers made by EPSON for the American, European, and Pacific markets (excluding Japan). Listed first are 24/48-pin printers followed by 9-pin printers.

Please note the following:

The year listed under "Year introduced" is approximate; models debut at different times in different countries.

Even though the market region is listed as America, Europe, or Pacific, not all countries in those regions may market that particular printer.

The same model name may appear several times because the features or commands available on that printer changed from approximately the date listed.

The last digit of some option model numbers varies depending on where the option is sold; however, the option itself is the same no matter where it is purchased.

The buffer size is adjustable by DIP switch or SelecType on many printers. Always make sure the buffer is set to the highest size before defining user-defined (download) characters.

24/48-Pin Printers

ActionPrinter L-750

Year introduced: 1989

Market: America

Built-in features

Print method	24-pin impact				
Speed	LQ	60 cps @ 10 cpi	72 cps @ 12 cpi		
	Draft	180 cps @ 10 cpi	216 cps @ 12 cpi		
Print width	8 inches				
Paper types	Continuous, Single sheets				
Multipart forms	Original plus 2 copies				
Paper paths	Rear, Top				
Tractor	Pull				
Paper parking	Not available				
Buffer size	8KB or 1KB				
Interface	Parallel				
Fonts (typefaces)	Roman, Sans Serif				

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Interfaces	#8148, #8165, #8172
Ribbon	#7753 (Fabric)

ActionPrinter L-750 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain				
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF				
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF				
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF				
Font	Draft			Sans Serif			Not used					
1-4	ON			ON			OFF	OFF				
1-5	ON			OFF			ON	OFF				
	ON			OFF								
1-6	Condensed printing			Noncondensed printing								
1-7	Graphics character table			Italics character table								
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off								
2-1	12-inch page length			11-inch page length								
2-2	Cut-sheet feeder page length 65 lines			Cut-sheet feeder page length 61 lines								
2-3	1-inch skip-over-perforation			No skip-over-perforation								
2-4	CR command produces a line feed			CR command does not produce a line feed								
2-5	8-KB buffer			1-KB buffer								
2-6	Bidirectional printing possible			Unidirectional printing only								
Pitch	Proportional		12 cpi	15 cpi	10 cpi							
2-7	ON			ON	OFF							
2-8	ON			OFF	ON							

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Interfaces	#8143, #8145, #8148, #8149, #8149M, #8161, #8165, #8172, #8172M
Ribbon	#7753 (Fabric)
Font cartridges	#7400, #7401, #7402, #7403, #7407

ActionPrinter L-1000 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain				
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF				
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF				
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF				
Font	Draft			Sans Serif	Font Cartridge		Roman					
1-4	ON	ON		OFF	OFF		OFF					
1-5	ON	OFF		OFF	ON		OFF					
	ON			OFF								
1-6	Condensed printing			Noncondensed printing								
1-7	Graphics character table			Italics character table								
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off								
2-1	12-inch page length			11-inch page length								
2-2	Cut-sheet feeder page length 65 lines			Cut-sheet feeder page length 61 lines								
2-3	1-inch skip-over-perforation			No skip-over-perforation								
2-4	CR command produces a line feed			CR command does not produce a line feed								
2-5	8-KB buffer			1-KB buffer								
2-6	Bidirectional printing possible			Unidirectional printing only								
Pitch	Proportional		12 cpi	15 cpi	10 cpi							
2-7	ON		ON	OFF	OFF							
2-8	ON		OFF	ON	OFF							

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top, Bottom		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Interfaces	#8143, #8148, #8165
Ribbons	#7753 (Fabric), #7768 (Film)

ActionPrinter 3000 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain								
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF								
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF								
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF								
Character table (1-7 ON)	PC437			PC850	PC860	PC863	PC865									
1-1	ON	ON			ON	ON	OFF									
1-2	ON	ON			OFF	OFF	ON									
1-3	ON	OFF			ON	OFF	ON									
Font	Draft	Prest.	OCR-B	Roman	Orator	S.Serif	Scr.	Cour.								
1-4	ON	ON	ON	ON	OFF	OFF	OFF	OFF								
1-5	ON	ON	OFF	OFF	ON	ON	OFF	OFF								
1-6	ON	OFF	ON	OFF	ON	OFF	ON	OFF								
1-7	ON Graphics character tables			OFF Italics character table												
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off												
Paper length (1-8 ON)	65 lines (letter size)				61 lines (A4)											
2-1	ON	ON			OFF	OFF										
2-2	ON	OFF			ON	OFF										
Paper length (1-8 OFF)	11.7 inches		12 inches		8.5 inches	11 inches										
2-1	ON	ON			OFF	OFF										
2-2	ON	OFF			ON	OFF										
2-3	ON CR command produces a line feed				OFF CR command does not produce a line feed											
2-4	8-KB buffer				1-KB buffer											
2-5	Bidirectional printing possible				Unidirectional printing only											
2-6	1-inch skip-over-perforation				No skip-over-perforation											
Pitch	20 cpi	12 cpi		17 cpi	10 cpi											
2-7	ON	ON		OFF	OFF											
2-8	ON	OFF		ON	OFF											

ActionPrinter 3250**Year introduced: 1991****Market: America*****Built-in features***

Print method	24-pin impact		
Speed	LQ	60 cps @ 10 cpi	72 cps @ 12 cpi
	Draft	167 cps @ 10 cpi	200 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 1 copy		
Paper paths	Rear, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	11KB or 1.75KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		

Options (with model numbers)

Tractor	C800262 (Push)
Ribbon	S015032 (Fabric)

ActionPrinter 3250 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC850, PC860, PC863, PC865
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Tear-off position	On or Above tear-off edge
Top-of-form position	-3, -2, -1, ±0, 1, 2, 3
Graphics printing direction	Unidirectional or Bidirectional
Download character memory	On or Off
Auto line feed	On or Off
Hex dump/demonstration	Hex dump mode or Demonstration printout

Built-in features

Print method	24-pin impact		
Speed	LQ	66 cps @ 10 cpi	79 cps @ 12 cpi
	Draft	180 cps @ 10 cpi	216 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 1 copy		
Paper paths	Rear, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	11KB, 1.75KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		
Nonprintable area	5.3 mm at the top of single sheets		

Options (with model numbers)

Color upgrade kit	C83201*
Tractor	C80026* (Pull)
Ribbon	S015060 (Fabric), S015061 (Color)

*The last digit of the option model numbers shown above as an asterisk varies by country.

ActionPrinter 3260 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC850, PC860, PC863, PC865, PC861, BRASCII, Abicomp, Italic
Page length (for continuous paper)	8.5, 11, 12, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Tear-off position	On or Above cutter
Graphic print direction	Unidirectional or Bidirectional
TOF position	-3, -2, -1, ±0, 1, 2, 3
Download	On or Off
Auto line feed	On or Off
Hex dump/Demonstration	Hex dump or Demonstration

Built-in features

Print method	24-pin impact
Speed	LQ 50 cps @ 10 cpi 60 cps @ 12 cpi Draft 150 cps @ 10 cpi 180 cps @ 12 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Labels
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	8KB or 1KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridge	#7407

ActionPrinter 4000 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
Font	Draft			Sans Serif			Font Cartridge				
1-4	ON	ON			OFF			OFF			
1-5	ON	OFF			ON			OFF			
	ON				OFF						
1-6	Condensed printing				Noncondensed printing						
1-7	Graphics character table				Italics character table						
1-8	Cut-sheet feeder mode on				Cut-sheet feeder mode off						
2-1	12-inch page length				11-inch page length						
2-2	Automatic tear-off				No automatic tear-off						
2-3	1-inch skip-over-perforation				No skip-over-perforation						
2-4	CR command produces a line feed				CR command does not produce a line feed						
2-5	8-KB buffer				1-KB buffer						
2-6	Bidirectional printing possible				Unidirectional printing only						
Pitch	Proportional		12 cpi		15 cpi		10 cpi				
2-7	ON		ON		OFF		OFF				
2-8	ON		OFF		ON		OFF				

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Interfaces	#8143, #8148, #8165, C823032, C823021
Ribbons	#7753 (Fabric), #7768 (Film)

ActionPrinter 4000 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain						
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF						
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF						
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF						
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865								
1-1	ON	ON	ON	ON	ON	OFF								
1-2	ON	ON	ON	OFF	OFF	ON								
1-3	ON	OFF	ON	ON	OFF	ON								
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches								
1-4	ON	ON	ON	OFF	OFF	OFF								
1-5	ON	OFF	ON	ON	ON	OFF								
		ON			OFF									
1-6	Condensed printing			Noncondensed printing										
1-7	Graphics character tables			Italics character table										
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off										
2-1	Not used			Not used										
2-2	Automatic tear-off			No automatic tear-off										
2-3	1-inch skip-over-perforation			No skip-over-perforation										
2-4	CR command produces a line feed			CR command does not produce a line feed										
2-5	8-KB buffer			1-KB buffer										
2-6	Bidirectional printing possible			Unidirectional printing only										
		Pitch			12 cpi	15 cpi	10 cpi							
2-7	ON	Proportional	ON	ON	OFF	OFF	OFF							
2-8	ON		OFF		ON		OFF							

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806242 (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165, #8172
Ribbons	#7754 (Fabric), #7770 (Film)
Font cartridge	#7407

ActionPrinter 4500 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Font	Draft		Sans Serif		Font Cartridge		Roman	
1-4	ON		ON		OFF		OFF	
1-5	ON		OFF		ON		OFF	
	ON			OFF				
1-6	Condensed printing			Noncondensed printing				
1-7	Graphics character table			Italics character table				
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off				
2-1	12-inch page length			11-inch page length				
2-2	Automatic tear-off			No automatic tear-off				
2-3	1-inch skip-over-perforation			No skip-over-perforation				
2-4	CR command produces a line feed			CR command does not produce a line feed				
2-5	8-KB buffer			1-KB buffer				
2-6	Bidirectional printing possible			Unidirectional printing only				
Pitch	Proportional		12 cpi		15 cpi		10 cpi	
2-7	ON		ON		OFF		OFF	
2-8	ON		OFF		ON		OFF	

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806242 (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165, C823032, C823021
Ribbons	#7754 (Fabric), #7770 (Film)

ActionPrinter 4500 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865				
1-1	ON	ON	ON	ON	ON	OFF				
1-2	ON	ON	ON	OFF	OFF	ON				
1-3	ON	OFF	ON	ON	OFF	ON				
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches				
1-4	ON	ON	ON	OFF	OFF	OFF				
1-5	ON	OFF	ON	ON	ON	OFF				
1-6		ON			OFF					
Condensed printing					Noncondensed printing					
1-7		Graphics character tables			Italics character table					
1-8		Cut-sheet feeder mode on			Cut-sheet feeder mode off					
2-1		Not used			Not used					
2-2		Automatic tear-off			No automatic tear-off					
2-3		1-inch skip-over-perforation			No skip-over-perforation					
2-4		CR command produces a line feed			CR command does not produce a line feed					
2-5		8-KB buffer			1-KB buffer					
2-6		Bidirectional printing possible			Unidirectional printing only					
Pitch		Proportional		12 cpi	15 cpi	10 cpi				
2-7		ON		ON	OFF	OFF				
2-8		ON		OFF	ON	OFF				

ActionPrinter 5000**Year introduced: 1991****Market: America****Built-in features**

Print method	24-pin impact
Speed	LQ 70 cps @ 10 cpi 84 cps @ 12 cpi Draft 210 cps @ 10 cpi 252 cps @ 12 cpi High-speed draft 225 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top, Bottom, Front
Tractors	Push, Pull
Paper parking	Available
Buffer size	8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C

Options (with model numbers)

Cut-sheet feeders	C806372, C806382 (Single-bin)
Tractor	C800192 (Pull)
Interfaces	C823061, C823081, C806382
Ribbons	#7753 (Fabric), #7768 (Film)

ActionPrinter 5000 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865			
1-1	ON	ON	ON	ON	OFF			
1-2	ON	ON	OFF	OFF	OFF			
1-3	ON	OFF	ON	ON	OFF			
	ON				OFF			
1-4	Graphics character tables				Italics character table			
1-5	Unidirectional printing only				Bidirectional printing possible			
1-6	High-speed draft printing				Normal draft printing			
1-7	No buffer				8-KB buffer			
1-8	1-inch skip-over-perforation				No skip-over-perforation			
Paper length	11.7 inches	12 inches	8.5 inches	11 inches				
2-1	ON	ON	OFF	OFF	ON			
2-2	ON	OFF	ON	OFF	ON			
	ON				OFF			
2-3	Automatic tear-off				No automatic tear-off			
2-4	CR command produces a line feed				CR does not cause a line feed			

ActionPrinter 5000+**Year introduced: 1992****Market: America****Built-in features**

Print method	24-pin impact
Speed	LQ 75 cps @ 10 cpi 90 cps @ 12 cpi Draft 225 cps @ 10 cpi 269 cps @ 12 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top, Bottom, Front
Tractors	Push, Pull
Paper parking	Available
Buffer size	0, 8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator-S, Script C, Roman T, Sans Serif H
Nonprintable area	5.3 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeders	C80637* (Single-bin), C80638* (High-capacity)
Tractor	C80019* (Pull)
Interfaces	C82305*, C82307*, C82310*
Ribbons	#7753 (Fabric), #7768 (Film)

*The last digit of the option model numbers shown above as an asterisk varies by country.

ActionPrinter 5000+ DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark I	Sweden	Italy	Spain I				
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF				
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF				
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF				
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865	BRASCI	Abicomp					
1-1	ON	ON	ON	ON	OFF	OFF	OFF					
1-2	ON	ON	OFF	OFF	ON	ON	OFF					
1-3	ON	OFF	ON	OFF	ON	OFF	ON					
	ON			OFF								
1-4	Graphics character tables			Italics character table								
1-5	Unidirectional printing only			Bidirectional printing possible								
1-6				No function								
1-7	No buffer			8-KB buffer								
1-8	1-inch skip-over-perforation			No skip-over-perforation								
Paper length	11.7 inches		12 inches		8.5 inches		11 inches					
2-1	ON		ON		OFF		OFF					
2-2	ON		OFF		ON		OFF					
	ON			OFF								
2-3	Automatic tear-off			No automatic tear-off								
2-4	Auto line feed			No auto line feed								

ActionPrinter 5500**Year introduced: 1991****Market: America****Built-in features**

Print method	24-pin impact
Speed	LQ 70 cps @ 10 cpi 84 cps @ 12 cpi Draft 210 cps @ 10 cpi 252 cps @ 12 cpi High-speed draft 225 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top, Bottom, Front
Tractors	Push, Pull
Paper parking	Available
Buffer size	8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C

Options (with model numbers)

Cut-sheet feeders	C80639*, C80640* (Single-bin)
Tractor	C80022* (Pull)
Interfaces	C82305*, C82306*, C82307*, C82308*
Ribbons	#7754 (Fabric), #7770 (Film)

*The last digit of the option model numbers shown above as an asterisk varies by country.

ActionPrinter 5500 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain						
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF						
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF						
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF						
Character table (1-4 ON)		PC437	PC850	PC860	PC863	PC865								
1-1	ON	ON	ON	ON	ON	OFF								
1-2	ON	ON	ON	OFF	OFF	ON								
1-3	ON	OFF	ON	ON	OFF	ON								
		ON			OFF									
1-4	Graphics character tables			Italics character table										
1-5	Unidirectional printing only			Bidirectional printing possible										
1-6	High-speed draft printing			Normal draft printing										
1-7	No buffer			8-KB buffer										
1-8	1-inch skip-over-perforation			No skip-over-perforation										
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches								
2-1	ON	ON	ON	OFF	OFF	OFF								
2-2	ON	OFF	ON	ON	OFF	OFF								
		ON			OFF									
2-3	Automatic tear-off			No automatic tear-off										
2-4	CR command produces a line feed			CR command does not produce a line feed										

Built-in features

Print method	24-pin impact				
Speed	LQ	75 cps @ 10 cpi	90 cps @ 12 cpi		
	Draft	225 cps @ 10 cpi	270 cps @ 12 cpi		
Print width	13.6 inches				
Paper types	Continuous, Single sheets, Envelopes, Labels				
Multipart forms	Original plus 5 copies				
Paper paths	Rear, Top, Front				
Tractor	Push				
Paper parking	Available				
Buffer size	8KB				
Interfaces	Parallel, Serial				
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S				

Options (with model numbers)

Cut-sheet feeder	C806301 (Single-bin)
Ribbons	S015013 (Fabric), #7764 (Film), #7763 (Color)

DLQ-2000 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
					ON	OFF					
1-4	Graphics character table			Italics character table							
1-5	Bidirectional printing possible			Unidirectional printing only							
1-6	Color/film ribbon			Ribbon (Fabric)							
1-7	Automatic tear-off			No automatic tear-off							
1-8	1-inch skip-over-perforation			No skip-over-perforation							
Paper length	11.7 inches	12 inches	8.5 inches	11 inches							
2-1	ON	ON	OFF	OFF							
2-2	ON	OFF	ON	OFF							
Interface	Parallel	Serial (even)	Serial (odd)	Serial (none)							
2-3	ON	ON	OFF	OFF							
2-4	ON	OFF	ON	OFF							
Baud	300	19,200	1,200	9,600							
2-5	ON	ON	OFF	OFF							
2-6	ON	OFF	ON	OFF							
		ON	OFF								
2-7	XON/XOFF protocol			DTR protocol							
2-8	CR command produces a line feed			CR command does not produce a line feed							

Built-in features

Print method	24-pin impact		
Speed	LQ	120 cps @ 10 cpi	144 cps @ 12 cpi
	Draft	360 cps @ 10 cpi	432 cps @ 12 cpi
	High-speed draft		444 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 5 copies		
Paper paths	Rear, Top, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	128KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, Script C, Orator, Orator S, OCR B, Roman T, Sans Serif H		
Nonprintable area	4.2 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	C80630* (Single-bin)
Interfaces	C82307*, C82308*, C82310*, C82312*, C82313*, C82314*, C82315*
Ribbons	S015066 (Fabric), S015608 (Film), S015067 (Color)

*The last digit of the option model numbers shown above as an asterisk varies by country.

DLQ-3000 SelectType settings

This printer has no DIP switches; however, the following settings can be made with SelectType.

SelectType Level 1 Features	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC864*, PC865, PC866*, PC869*, ISO Latin 1T*, ISO 8859-7*, MAZOWIA*, Code MJK*, Bulgaria*, BRASCI, Abicomp
Page tractor	8.5 inches, 11 inches, 12 inches, 70/6 (A4) inches, or Other (24 to 132 lines)
Page CSF	A4, Letter, or Other (24 to 132 lines)
Line spacing	1/6 inch or 1/8 inch
T-margin tractor, T-margin manual, or T-margin CSF	0.2, 0.33, or 1 inch, in 1/180-inch increments
Left margin	0 to 80 columns
Right margin	1 to 136 columns
B-margin tractor	0 to 1 inch, in 1/180-inch increments
Graphics printing direction	Bidirectional or Unidirectional

*Availability varies by country.

SelectType Level 2 Features	Options
Language	English, French, German, Italian, or Spanish
Software	ESC/P 2 or IBM XL24E
Interface	Auto Selection, Parallel, RS-232C, or Optional Slot
I/F timeout	1, 10, or 256 sec.
Input buffer	On or Off
Baud rate	300, 600, 1,200, 2,400, 4,800, 9,600, or 19,200 bps
Parity	None, Even, Odd, or Ignore
Auto tear off	On or Off
Auto LF	On or Off
Auto CR	On or Off †
AGM (Alternate Graphics Mode)	On or Off
Copy mode	Copy 1 or Copy 2
Standard setting (Default settings)	—

† This setting is available only in IBM mode.

Built-in features

Print method	24-pin impact		
Speed	LQ	120 cps @ 10 cpi	144 cps @ 12 cpi
	Draft	360 cps @ 10 cpi	432 cps @ 12 cpi
	High-speed draft		444 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 5 copies		
Paper paths	Rear, Top, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	128KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, Script C, Orator, Orator S, OCR B, Roman T, Sans Serif H		
Bar codes	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET		
Nonprintable area	4.2 mm at the top and bottom of single sheets		

Options (with model numbers)

Cut-sheet feeder	
Interfaces	
	C82315*, C82331*
	S015066 (Fabric), S015608 (Film), S015067 (Color)

DLQ-3000 ('96 ~) SelectType settings

SelectType Level 1 Features	Options
Character table	Italic, PC437, PC437 Greek*, PC774*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC864*, PC865, PC866*, PC866 LAT*, PC869*, ISO Latin1, ISO Latin 1T*, ISO 8859-2*, ISO 8859-7*, MAZOWIA*, Coda MJK*, Bulgaria*, BRASCI, Abicomp, Estonia*, Roman 8
Page tractor	8.5 inches, 11 inches, 12 inches, 70/6 (A4) inches, or Other (24 to 132 lines)
Page CSF	A4, Letter, or Other (24 to 132 lines)
Line spacing	1/6 inch or 1/8 inch
T-margin tractor, T-margin manual, or T-margin CSF	0.2 to 1 inch, in 1/180-inch increments
Left margin	0 to 80 columns
Right margin	1 to 136 columns
B-margin tractor	0 to 1 inch, in 1/180-inch increments
Graphics printing direction	Bidirectional or Unidirectional

*Availability varies by country.

SelectType Level 2 Features	Options
Language	English, French, German, Italian, or Spanish
Software	ESC/P 2 or IBM 2391 Plus
Interface	Auto Selection, Parallel, RS-232C, or Optional Slot
I/F timeout	1 to 255 sec.
Input buffer	On or Off
Baud rate	300, 600, 1,200, 2,400, 4,800, 9,600, or 19,200 bps
Parity	None, Even, Odd, or Ignore
Auto tear off	On or Off
Auto LF	On or Off
Auto CR	On or Off †
AGM (Alternate Graphics Mode)	On or Off †
Copy mode	Copy 1 or Copy 2
Standard setting (Default settings)	—

† This setting is available only in IBM mode.

Built-in features

Print method	24-pin impact		
Speed	LQ	60 cps @ 10 cpi	72 cps @ 12 cpi
	Draft	167 cps @ 10 cpi	200 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 1 copy		
Paper paths	Rear, Front		
Tractor	Push		
Paper parking	Not available	Buffer size	11KB or 1.75KB
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		

Options (with model numbers)

Tractor	C800262 (Push)
Ribbon	S015032 (Fabric)

LQ-100 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC863, PC864*, PC865, PC866*, PC869*, U.S.S.R. GOST*
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Tear-off position	On or Above tear-off edge
Top-of-form position	-3, -2, -1, ±0, 1, 2, 3
Graphics printing direction	Unidirectional or Bidirectional
Download character memory	On or Off
Auto line feed	On or Off
Hex dump/demonstration	Hex dump mode or Demonstration printout

*Availability varies by country.

Built-in features

Print method	24-pin impact		
Speed	LQ	66 cps @ 10 cpi	79 cps @ 12 cpi
	Draft	180 cps @ 10 cpi	216 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 1 copy		
Paper paths	Rear, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	11KB, 1.75KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		
Nonprintable area	5.3 mm at the top of single sheets		

Options (with model numbers)

Color upgrade kit	C83201*
Tractor	C80026* (Pull)
Ribbon	S015060 (Fabric), S015061 (Color)

*The last digit of the option model numbers shown as an asterisk varies by country.

LQ-150 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC850, PC860, PC863, PC865, PC861, BRASCII, Abicomp, Italic
Page length (for continuous paper)	8.5, 11, 12, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Tear-off position	On or Above cutter
Graphic print direction	Unidirectional or Bidirectional
TOF position	-3, -2, -1, ±0, 1, 2, 3
Download	On or Off
Auto line feed	On or Off
Hex dump/Demonstration	Hex dump or Demonstration

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top, Bottom		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Interfaces	#8143, #8148, #8165
Ribbons	#7753 (Fabric), #7768 (Film)

LQ-200 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865				
1-1	ON	ON	ON	ON	ON	OFF				
1-2	ON	ON	OFF	OFF	OFF	ON				
1-3	ON	OFF	ON	ON	OFF	ON				
Font	Draft	Prest.	OCR-B	Roman	Orator	S.Serif	Scr.	Cour.		
1-4	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-5	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-6	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
1-7		ON Graphics character tables			OFF Italics character table					
1-8		Cut-sheet feeder mode on			Cut-sheet feeder mode off					
Paper length 1-8 ON	65 lines (letter size)			61 lines (A4)						
2-1	ON	ON	ON	OFF	OFF	OFF				
2-2	ON	OFF	ON	ON	ON	OFF				
Paper length 1-8 OFF	11.7 inches		12 inches	8.5 inches	8.5 inches	11 inches				
2-1	ON	ON	ON	OFF	OFF	OFF				
2-2	ON	OFF	ON	ON	ON	OFF				
2-3		ON CR command produces a line feed			OFF CR command does not produce a line feed					
2-4		8-KB buffer			1-KB buffer					
2-5		Bidirectional printing possible			Unidirectional printing only					
2-6		1-inch skip-over-perforation			No skip-over-perforation					
Pitch	20 cpi	12 cpi	17 cpi	17 cpi	17 cpi	10 cpi				
2-7	ON	ON	OFF	OFF	OFF	OFF				
2-8	ON	OFF	ON	ON	ON	OFF				

Built-in features

Print method	24-pin impact		
Speed	LQ	80 cps @ 10 cpi	96 cps @ 12 cpi
Print width	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Paper types	8 inches		
Multipart forms	Continuous, Single sheets, Envelopes, Labels		
Paper paths	Original plus 1 copy		
Tractor	Rear, Front		
Paper parking	Push		
Buffer size	Available		
Download memory	8KB		
Interface	11KB		
Fonts (typefaces)	Parallel, Serial		
	Roman, Sans Serif, Courier, Prestige, Script		

Options (with model numbers)

Color upgrade kit	C83211*
Cut-sheet feeder	C80637*
Tractor	C80030* (Pull)
Ribbon	#7753 (Fabric), #7768 (Film), S015077 (Color)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-300 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC850, PC860, PC863, PC865, PC861, BRASCI, Abicomp, PC437 Greek*, PC869*, ISO 8859-7*, PC853*, PC857*, ISO Latin 1T*, PC855*, PC866*, PC852*, MAZOWIA*, Code MJK*, Bulgarian, PC864*, Italic
Page length (for continuous paper)	8.5, 11, 12, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Auto tear off	On or Off
Graphics printing direction	Unidirectional or Bidirectional
Software emulation	ESC/P 2 or IBM XL24E
AGM (Alternate Graphics Mode)	On or Off †
Auto line feed	On or Off
Interface	Auto (10 sec. wait), Auto (30 sec. wait), Parallel, Serial
Bit rate	300, 600, 1,200, 2,400, 4,800, 9,600, 19,200
Parity bit	None, Odd, Even
Data length	7 bit or 8 bit
EXT/ACK	Disable or Enable
State reply	On or Off

*Availability varies by country.

† This setting is available only in IBM mode.

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Interfaces	#8143, #8145, #8148
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridges	#7400, #7401, #7402, #7403

LQ-400 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Font	Draft			Font Cartridge			Roman			
1-4	ON	ON		OFF			OFF			
1-5	ON	OFF		ON			OFF			
	ON			OFF						
1-6	Condensed printing			Noncondensed printing						
1-7	Graphics character table			Italics character table						
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off						
2-1	12-inch page length			11-inch page length						
2-2	Cut-sheet feeder page length 65 lines			Cut-sheet feeder page length 61 lines						
2-3	1-inch skip-over-perforation			No skip-over-perforation						
2-4	CR command produces a line feed			CR command does not produce a line feed						
2-5	8-KB buffer			1-KB buffer						
2-6	Bidirectional printing possible			Unidirectional printing only						
Pitch	Proportional		12 cpi	15 cpi	10 cpi					
2-7	ON		ON	OFF	OFF					
2-8	ON		OFF	ON	OFF					

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Interfaces	#8143, #8148, #8165, C823032, C823021
Ribbons	#7753 (Fabric), #7768 (Film)

LQ-450 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865				
1-1	ON	ON	ON	ON	ON	OFF				
1-2	ON	ON	OFF	OFF	OFF	ON				
1-3	ON	OFF	ON	ON	OFF	ON				
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches				
1-4	ON	ON	ON	OFF	OFF	OFF				
1-5	ON	OFF	ON	ON	ON	OFF				
1-6		ON			OFF					
Condensed printing					Noncondensed printing					
1-7		Graphics character tables			Italics character table					
1-8		Cut-sheet feeder mode on			Cut-sheet feeder mode off					
2-1		Not used			Not used					
2-2		Automatic tear-off			No automatic tear-off					
2-3		1-inch skip-over-perforation			No skip-over-perforation					
2-4		CR command produces a line feed			CR command does not produce a line feed					
2-5		8-KB buffer			1-KB buffer					
2-6		Bidirectional printing possible			Unidirectional printing only					
Pitch		Proportional		12 cpi	15 cpi	10 cpi				
2-7		ON		ON	OFF	OFF				
2-8		ON		OFF	ON	OFF				

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Interfaces	#8143, #8145, #8148, #8149, #8149M, #8161, #8165, #8172, #8172M
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridges	#7400, #7401, #7402, #7403

LQ-500 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain				
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF				
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF				
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF				
Font	Draft			Sans Serif	Font Cartridge		Roman					
1-4	ON	ON		OFF	OFF		OFF					
1-5	ON	OFF		OFF	ON		OFF					
	ON			OFF								
1-6	Condensed printing			Noncondensed printing								
1-7	Graphics character table			Italics character table								
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off								
2-1	12-inch page length			11-inch page length								
2-2	Cut-sheet feeder page length 65 lines			Cut-sheet feeder page length 61 lines								
2-3	1-inch skip-over-perforation			No skip-over-perforation								
2-4	CR command produces a line feed			CR command does not produce a line feed								
2-5	8-KB buffer			1-KB buffer								
2-6	Bidirectional printing possible			Unidirectional printing only								
Pitch	Proportional	12 cpi	15 cpi	10 cpi								
2-7	ON	ON	OFF	OFF								
2-8	ON	OFF	ON	OFF								

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806121 (Single-bin)
Tractor	C800061 (Pull)
Interfaces	#8143, #8148, #8165, #8172
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridge	#7407

LQ-510 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain						
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF						
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF						
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF						
Font	Draft			Sans Serif	Font Cartridge		Roman							
1-4	ON	ON		OFF	OFF		OFF							
1-5	ON	OFF		OFF	ON		OFF							
	ON			OFF										
1-6	Condensed printing			Noncondensed printing										
1-7	Graphics character table			Italics character table										
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off										
2-1	12-inch page length			11-inch page length										
2-2	Automatic tear-off			No automatic tear-off										
2-3	1-inch skip-over-perforation			No skip-over-perforation										
2-4	CR command produces a line feed			CR command does not produce a line feed										
2-5	8-KB buffer			1-KB buffer										
2-6	Bidirectional printing possible			Unidirectional printing only										
Pitch	Proportional		12 cpi	15 cpi	10 cpi									
2-7	ON		ON	OFF	OFF									
2-8	ON		OFF	ON	OFF									

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Interfaces	#8143, #8148, #8165, C823032, C823021
Ribbons	#7753 (Fabric), #7768 (Film)

LQ-510 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865				
1-1	ON	ON	ON	ON	ON	OFF				
1-2	ON	ON	ON	OFF	OFF	ON				
1-3	ON	OFF	ON	ON	OFF	ON				
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches				
1-4	ON	ON	ON	OFF	OFF	OFF				
1-5	ON	OFF	ON	ON	ON	OFF				
1-6		ON Condensed printing			OFF Noncondensed printing					
1-7		Graphics character tables			Italics character table					
1-8		Cut-sheet feeder mode on			Cut-sheet feeder mode off					
2-1		Not used			Not used					
2-2		Automatic tear-off			No automatic tear-off					
2-3		1-inch skip-over-perforation			No skip-over-perforation					
2-4		CR command produces a line feed			CR command does not produce a line feed					
2-5		8-KB buffer			1-KB buffer					
2-6		Bidirectional printing possible			Unidirectional printing only					
Pitch		Proportional	12 cpi	15 cpi	15 cpi	10 cpi				
2-7		ON	ON	OFF	OFF	OFF				
2-8		ON	OFF	ON	ON	OFF				

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridge	#7407

LQ-550 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain								
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF								
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF								
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF								
Font	Draft			Sans Serif	Font Cartridge		Roman									
1-4	ON	ON			OFF	OFF										
1-5	ON	OFF			ON	OFF										
	ON				OFF											
1-6	Condensed printing				Noncondensed printing											
1-7	Graphics character table				Italics character table											
1-8	Cut-sheet feeder mode on				Cut-sheet feeder mode off											
2-1	12-inch page length				11-inch page length											
2-2	Automatic tear-off				No automatic tear-off											
2-3	1-inch skip-over-perforation				No skip-over-perforation											
2-4	CR command produces a line feed				CR command does not produce a line feed											
2-5	8-KB buffer				1-KB buffer											
2-6	Bidirectional printing possible				Unidirectional printing only											
Pitch	Proportional		12 cpi		15 cpi		10 cpi									
2-7	ON		ON		OFF		OFF									
2-8	ON		OFF		ON		OFF									

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Interfaces	#8143, #8148, #8165, C823032, C823021
Ribbons	#7753 (Fabric), #7768 (Film)

LQ-550 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865				
1-1	ON	ON	ON	ON	ON	OFF				
1-2	ON	ON	ON	OFF	OFF	ON				
1-3	ON	OFF	ON	ON	OFF	ON				
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches				
1-4	ON	ON	ON	OFF	OFF	OFF				
1-5	ON	OFF	ON	ON	ON	OFF				
1-6		ON Condensed printing			OFF Noncondensed printing					
1-7		Graphics character tables			Italics character table					
1-8		Cut-sheet feeder mode on			Cut-sheet feeder mode off					
2-1		Not used			Not used					
2-2		Automatic tear-off			No automatic tear-off					
2-3		1-inch skip-over-perforation			No skip-over-perforation					
2-4		CR command produces a line feed			CR command does not produce a line feed					
2-5		8-KB buffer			1-KB buffer					
2-6		Bidirectional printing possible			Unidirectional printing only					
Pitch		Proportional	12 cpi	15 cpi	10 cpi					
2-7		ON	ON	OFF	OFF					
2-8		ON	OFF	ON	OFF					

Built-in features

Print method	24-pin impact		
Speed	LQ	70 cps @ 10 cpi	84 cps @ 12 cpi
	Draft	210 cps @ 10 cpi	252 cps @ 12 cpi
	High-speed draft		225 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top, Bottom, Front		
Tractors	Push, Pull		
Paper parking	Available		
Buffer size	8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C		

Options (with model numbers)

Cut-sheet feeders	C80637*, C80638* (Single-bin)
Tractor	C80019* (Pull)
Interfaces	C82305*, C82307*, C82310*
Ribbons	#7753 (Fabric), #7768 (Film)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-570 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain						
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF						
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF						
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF						
Character table (1-4 ON)			PC437	PC850	PC860	PC863	PC865							
1-1	ON	ON	ON	ON	ON	ON	OFF							
1-2	ON	ON	ON	OFF	OFF	OFF	ON							
1-3	ON	OFF	ON	ON	ON	OFF	ON							
		ON			OFF									
1-4	Graphics character tables			Italics character table										
1-5	Unidirectional printing only			Bidirectional printing possible										
1-6	High-speed draft printing			Normal draft printing										
1-7	No buffer			8-KB buffer										
1-8	1-inch skip-over-perforation			No skip-over-perforation										
Paper length		11.7 inches	12 inches	8.5 inches	11 inches									
2-1	ON	ON	ON	OFF	OFF									
2-2	ON	OFF	ON	ON	OFF									
		ON			OFF									
2-3	Automatic tear-off			No automatic tear-off										
2-4	CR command produces a line feed			CR command does not produce a line feed										

Year introduced: 1992
Market: America, Europe, Pacific

Built-in features

Print method	24-pin impact		
Speed	LQ	75 cps @ 10 cpi	90 cps @ 12 cpi
	Draft	225 cps @ 10 cpi	269 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top, Bottom, Front		
Tractors	Push, Pull		
Paper parking	Available		
Buffer size	0, 8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator-S, Script C, Roman T, Sans Serif H		
Nonprintable area	5.3 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	C80637* (Single-bin), C80638* (High-capacity)		
Tractor	C80019* (Pull)		
Interfaces	C82305*, C82307*, C82310*		
Ribbons	#7753 (Fabric), #7768 (Film)		

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-570+ DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark I	Sweden	Italy	Spain I
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865	BRASCI* PC437**	Abicomp* PC853**	PC437* PC852**
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF

*These character tables are not available on the European version.

**These character tables are available only on the European version.

	ON	OFF
1-4	Graphics character tables	Italics character table
1-5	Unidirectional printing only	Bidirectional printing possible
1-6	IBM emulation*	ESC/P 2
1-7	No buffer	8-KB buffer
1-8	1-inch skip-over-perforation	No skip-over-perforation

*DIP switch 1-6 functions only on the European version of this printer.

Paper length	11.7 inches	12 inches	8.5 inches	11 inches
2-1	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF

	ON	OFF
2-3	Automatic tear-off	No automatic tear-off
2-4	Auto line feed	No auto line feed

DIP-switch settings for IBM emulation mode

Character table (1-6 ON)	437	850	860	863	865	437 Greek	853	852
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
1-4	Character set 1	Character set 2
1-8	Alternate graphics mode on*	Alternate graphics mode off
2-1	12-inch page length (cont. paper)	11-inch page length (cont. paper)
2-2	Auto CR enabled	Auto CR disabled

*With DIP-switch 1-8 ON, ESC 3, ESC A, ESC J, and ESC * function the same as in ESC/P.

Built-in features

Print method	24-pin impact
Speed	LQ 83 cps @ 10 cpi 100 cps @ 12 cpi Draft 250 cps @ 10 cpi 300 cps @ 12 cpi High-speed draft 300 cpi @ 10 cpi
Print width	10.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels, Cards, Roll paper
Multipart forms	Original plus 4 copies
Paper paths	Rear, Front
Tractors	Push
Paper parking	Available
Buffer size	0, 64KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator-S, Script C, Roman T, Sans Serif H
Bar codes	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Nonprintable area	0 mm at the top and bottom of single sheets

Options (with model numbers)

Cut-sheet feeders	C80678* (High-capacity), C80679* (Second-bin)
Roll paper holder	#8310
Interfaces	C82305*, C82306*, C82307*, C82308*, C82310*, C82311*, C82312*, C82313*, C82314*, C82315*, C82331*, C82345*, C82346*
Ribbons	S015016

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-670 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Page length for tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Skip over perforation	On, Off, or Others
Auto tear off	On or Off
Auto line feed	On or Off
Print direction	Auto, Uni-d, or Bi-d
I/F mode	Auto, Parallel, or Option
Auto I/F wait time	10 or 30 sec.
Software	ESC/P 2 or IBM 2390 Plus
Character table	Italic, PC437, PC437 Greek*, PC774*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC864*, PC865, PC866*, PC866 LAT.*, PC869*, BRASCI, Abicomp, Roman 8, ISO Latin 1, MAZOWIA*, Code MJK*, ISO 8859-2*, ISO 8859-7*, ISO Latin 1T*, Bulgaria*, Estonia*,
International character set	U.S.A., France, Germany, U.K., Denmark, Sweden, Italy, Spain
0 slash	0 or Ø
High speed draft	On or Off
Input buffer	On or Off
Buzzer	On or Off
Auto CR	On or Off †
A.G.M.	On or Off †
Font	OCR-B, Orator, Orator-S, Script C, Roman T (PS), Sans Serif H (PS)

* Availability varies by country.

† This setting is available only in IBM mode.

Built-in features

Print method	24-pin impact
Speed	LQ 60 cps @ 10 cpi Draft 180 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 1 copy
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	7KB or 1KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeders	#7333 (Single-bin), #8347 (Double-bin)
Tractor	#7303 (Pull)
Interfaces	#8148, #8165, #8172
Ribbons	N/A
Font cartridges	#7400, #7401, #7402, #7403, #7404

LQ-800 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
						OFF		
1-4	ON 7-KB buffer						1-KB buffer	
1-5	Draft printing						LQ printing	
1-6	Condensed printing						Noncondensed printing	
1-7	1-inch skip-over-perforation						No skip-over-perforation	
1-8	Cut-sheet feeder mode on						Cut-sheet feeder mode off	
2-1	12-inch page length						11-inch page length	
2-2	Identity module						Internal firmware	
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel				
2-3	ON	ON	OFF	OFF				
2-4	ON	OFF	ON	OFF				
Baud	9,600	4,800	1,200	300				
2-5	ON	ON	OFF	OFF				
2-6	ON	OFF	ON	OFF				
		ON	OFF					
2-7	SLCT IN on			SLCT IN off				
2-8	CR command produces a line feed						CR command does not produce a line feed	

Built-in features

Print method	24-pin impact		
Speed	LQ	73 cps @ 10 cpi	88 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	#7339 (Single-bin), #7346 (Double-bin)
Tractor	#7311 (Pull)
Interfaces	#8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M)
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridge	#7407

LQ-850 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain				
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF				
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF				
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF				
						ON	OFF					
1-4	Graphics character table			Italics character table								
1-5	Unidirectional printing only			Bidirectional printing possible								
1-6	Not used			Not used								
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off								
1-8	No buffer			6-KB buffer								
2-1	12-inch page length			11-inch page length								
2-2	1-inch skip-over-perforation			No skip-over-perforation								
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel								
2-3	ON	ON	OFF	OFF								
2-4	ON	OFF	ON	OFF								
Baud	300	4,800	1,200	9,600								
2-5	ON	ON	OFF	OFF								
2-6	ON	OFF	ON	OFF								
		ON	OFF									
2-7	Automatic tear-off			No automatic tear-off								
2-8	CR command produces a line feed			CR command does not produce a line feed								

Built-in features

Print method	24-pin impact		
Speed	LQ	82 cps @ 10 cpi	98 cps @ 12 cpi
	Draft	246 cps @ 10 cpi	295 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeders	#7339 (Single-bin), #7346 (Double-bin)
Tractor	#7311 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7753 (Fabric), #7768 (Film)

LQ-850 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain								
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF								
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF								
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF								
Character table (1-4 ON)	PC437			PC850			PC860									
1-1	ON	ON			ON	ON										
1-2	ON	ON			OFF	OFF										
1-3	ON	OFF			ON	OFF										
	ON				OFF											
1-4	Graphics character tables				Italics character table											
1-5	Bidirectional printing possible				Unidirectional printing only											
1-6	Normal-speed draft				High-speed draft											
1-7	Cut-sheet feeder mode on				Cut-sheet feeder mode off											
1-8	1-inch skip-over-perforation				No skip-over-perforation											
Paper length	11.7 inches		12 inches		8.5 inches		11 inches									
2-1	ON	ON		OFF		OFF										
2-2	ON	OFF		ON		OFF										
Interface	Serial (none)		Serial (even)		Serial (odd)		Parallel									
2-3	ON	ON		OFF		OFF										
2-4	ON	OFF		ON		OFF										
Baud	300		19,200		1,200		9,600									
2-5	ON	ON		OFF		OFF										
2-6	ON	OFF		ON		OFF										
	ON				OFF											
2-7	Automatic tear-off				No automatic tear-off											
2-8	CR command produces a line feed				CR command does not produce a line feed											

Built-in features

Print method	24-pin impact		
Speed	LQ	82 cps @ 10 cpi	98 cps @ 12 cpi
	Draft	246 cps @ 10 cpi	295 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	#7339 (Single-bin), #7346 (Double-bin)
Tractor	#7311 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridge	#7407

LQ-850+ DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
						ON	OFF			
1-4	Graphics character table			Italics character table						
1-5	Unidirectional printing only			Bidirectional printing possible						
1-6	Normal draft			High-speed draft						
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off						
1-8	No buffer			6-KB buffer						
2-1	12-inch page length			11-inch page length						
2-2	1-inch skip-over-perforation			No skip-over-perforation						
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel						
2-3	ON	ON	OFF	OFF						
2-4	ON	OFF	ON	OFF						
Baud	300	19,200	1,200	9,600						
2-5	ON	ON	OFF	OFF						
2-6	ON	OFF	ON	OFF						
		ON	OFF							
2-7	Automatic tear-off			No automatic tear-off						
2-8	CR command produces a line feed			CR command does not produce a line feed						

Built-in features

Print method	24-pin impact		
Speed	LQ	75 cps @ 10 cpi	90 cps @ 12 cpi
	Draft	225 cps @ 10 cpi	270 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	C806141 (Single-bin), C806151 (Double-bin)
Tractor	C800071 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7762 (Fabric), #7764 (Film), #7763 (Color)
Font cartridge	#7407

LQ-860 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
ON								OFF
1-4	Graphics character table				Italics character table			
1-5	Unidirectional printing only				Bidirectional printing possible			
1-6	Normal-speed draft				High-speed draft			
1-7	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
1-8	No buffer				6-KB buffer			
2-1	12-inch page length				11-inch page length			
2-2	1-inch skip-over-perforation				No skip-over-perforation			
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel				
2-3	ON	ON	OFF	OFF				
2-4	ON	OFF	ON	OFF				
Baud	300	19,200	1,200	9,600				
2-5	ON	ON	OFF	OFF				
2-6	ON	OFF	ON	OFF				
ON		OFF						
2-7	Automatic tear-off			No automatic tear-off				
2-8	CR command produces a line feed			CR command does not produce a line feed				

Built-in features

Print method	24-pin impact		
Speed	LQ	82 cps @ 10 cpi	98 cps @ 12 cpi
	Draft	246 cps @ 10 cpi	295 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	Single bin: C806141 (Europe), C806271 (America); Double-bin: C806151 (Europe), C806281 (America)
Tractors	Pull: C800071 (Europe), C800161 (America)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7762 (Fabric), #7764 (Film), #7763 (Color)
Font cartridge	#7407

LQ-860 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865			
1-1	ON	ON	ON	ON	ON			OFF
1-2	ON	ON	OFF	OFF	OFF			ON
1-3	ON	OFF	ON	ON	OFF			ON
	ON			OFF				
1-4	Graphics character tables			Italics character table				
1-5	Unidirectional printing only			Bidirectional printing possible				
1-6	Normal-speed draft			High-speed draft				
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off				
1-8	1-inch skip-over-perforation			No skip-over-perforation				
Paper length	11.7 inches	12 inches	8.5 inches	11 inches				
2-1	ON	ON	OFF	OFF				
2-2	ON	OFF	ON	OFF				
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel				
2-3	ON	ON	OFF	OFF				
2-4	ON	OFF	ON	OFF				
Baud	300	19,200	1,200	9,600				
2-5	ON	ON	OFF	OFF				
2-6	ON	OFF	ON	OFF				
	ON			OFF				
2-7	Automatic tear-off			No automatic tear-off				
2-8	CR command produces a line feed			CR command does not produce a line feed				

Built-in features

Print method	24-pin impact
Speed	LQ 82 cps @ 10 cpi 98 cps @ 12 cpi Draft 246 cps @ 10 cpi 295 cps @ 12 cpi High-speed draft 300 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	6KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif

Options (with model numbers)

Cut-sheet feeders	C806141 (Single-bin), C806151 (Double-bin)
Tractor	C800071 (Pull) #8143, #8148, #8165, #8641, #8642
Interfaces	#7762 (Fabric), #7764 (Film), #7763 (Color)
Ribbons	
Font cartridge	#7407

LQ-860+ DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865						
1-1	ON	ON	ON	ON	OFF						
1-2	ON	ON	OFF	OFF	OFF						
1-3	ON	OFF	ON	ON	OFF						
	ON			OFF							
1-4	Graphics character tables			Italics character table							
1-5	Unidirectional printing only			Bidirectional printing possible							
1-6	Normal-speed draft			High-speed draft							
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off							
1-8	1-inch skip-over-perforation			No skip-over-perforation							
Paper length	11.7 inches	12 inches	8.5 inches	8.5 inches	8.5 inches	11 inches	11 inches	11 inches			
2-1	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF			
2-2	ON	OFF	ON	ON	ON	ON	ON	ON			
Interface	Serial (none)	Serial (even)	Serial (odd)	Serial (odd)	Serial (odd)	Parallel	Parallel	Parallel			
2-3	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF			
2-4	ON	OFF	ON	ON	ON	ON	ON	ON			
Baud	300	19,200	1,200	1,200	1,200	9,600	9,600	9,600			
2-5	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF			
2-6	ON	OFF	ON	ON	ON	ON	ON	ON			
	ON			OFF							
2-7	Automatic tear-off			No automatic tear-off							
2-8	CR command produces a line feed			CR command does not produce a line feed							

Year introduced: 1991
Market: America, Europe, Pacific

Built-in features

Print method	24-pin impact		
Speed	LQ	92 cps @ 10 cpi	110 cps @ 12 cpi
	Draft	275 cps @ 10 cpi	330 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top, Bottom, Front		
Tractors	Push, Pull		
Paper parking	Available		
Buffer size	64KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C		

Options (with model numbers)

Cut-sheet feeders	C80637*, C80638* (Single-bin)
Tractor	C80020* (Pull)
Interfaces	C82305*, C82306*, C80637*, C82308*
Ribbons	#7753 (Fabric), #7768 (Film)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-870 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain						
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF						
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF						
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF						
Character table (1-4 ON)		PC437	PC850	PC860	PC863	PC865								
1-1	ON	ON	ON	ON	ON	OFF								
1-2	ON	ON	ON	OFF	OFF	ON								
1-3	ON	OFF	ON	ON	OFF	ON								
		ON			OFF									
1-4	Graphics character tables			Italics character table										
1-5	Unidirectional printing only			Bidirectional printing possible										
1-6	High-speed draft printing			Normal draft printing										
1-7	No buffer			64-KB buffer										
1-8	1-inch skip-over-perforation			No skip-over-perforation										
Paper length		11.7 inches	12 inches	8.5 inches	PC863	PC865								
2-1	ON	ON	ON	OFF	ON	OFF								
2-2	ON	OFF	ON	ON	OFF	ON								
		ON			OFF									
2-3	Automatic tear-off			No automatic tear-off										
2-4	CR command produces a line feed			CR command does not produce a line feed										

Built-in features

Print method	24-pin impact		
Speed	LQ	73 cps @ 10 cpi	88 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
Print width	11 inches		
Paper types	Continuous, Single sheets, Envelopes		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	#7345 (Single-bin), #7347 (Double-bin)
Tractor	#7313 (Pull)
Interfaces	#8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M)
Ribbons	#7753 (Fabric), #7768 (Film)
Font cartridge	#7407

LQ-950 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
						ON	OFF			
1-4	Graphics character tables			Italics character table						
1-5	Unidirectional printing only			Bidirectional printing possible						
1-6	Not used			Not used						
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off						
1-8	No buffer			6-KB buffer						
2-1	12-inch page length			11-inch page length						
2-2	1-inch skip-over-perforation			No skip-over-perforation						
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel						
2-3	ON	ON	OFF	OFF						
2-4	ON	OFF	ON	OFF						
Baud	300	4,800	1,200	9,600						
2-5	ON	ON	OFF	OFF						
2-6	ON	OFF	ON	OFF						
		ON	OFF							
2-7	Automatic tear-off			No automatic tear-off						
2-8	CR command produces a line feed			CR command does not produce a line feed						

Built-in features

Print method	24-pin impact
Speed	LQ 60 cps @ 10 cpi Draft 180 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 1 copy
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	7KB or 1KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeders	#7334 (Single-bin), #8348 (Double-bin)
Tractor	#7304 (Pull)
Interfaces	#8148, #8165, #8172
Ribbons	N/A
Font cartridges	#7400, #7401, #7402, #7403

LQ-1000 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
						OFF		
1-4	ON 7-KB buffer						1-KB buffer	
1-5	Draft printing						LQ printing	
1-6	Condensed printing						Noncondensed printing	
1-7	1-inch skip-over-perforation						No skip-over-perforation	
1-8	Cut-sheet feeder mode on						Cut-sheet feeder mode off	
2-1	12-inch page length						11-inch page length	
2-2	Identity module						Internal firmware	
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel				
2-3	ON	ON	OFF	OFF				
2-4	ON	OFF	ON	OFF				
Baud	9,600	4,800	1,200	300				
2-5	ON	ON	OFF	OFF				
2-6	ON	OFF	ON	OFF				
		ON	OFF					
2-7	SLCT IN on			SLCT IN off				
2-8	CR command produces a line feed						CR command does not produce a line feed	

Built-in features

Print method	24-pin impact		
Speed	LQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C80624* (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642, #8172
Ribbons	#7754 (Fabric), #7770 (Film)
Font cartridge	#7407

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-1010 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain					
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF					
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF					
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF					
Font	Draft			Sans Serif	Font Cartridge		Roman						
1-4	ON	ON			OFF	OFF							
1-5	ON	OFF			ON	OFF							
1-6	ON			Condensed printing	OFF								
1-7	Graphics character table			Noncondensed printing	Italics character table								
1-8	Cut-sheet feeder mode on			Cut-sheet feeder mode off	Cut-sheet feeder mode off								
2-1	12-inch page length			11-inch page length	11-inch page length								
2-2	Automatic tear-off			No automatic tear-off	No automatic tear-off								
2-3	1-inch skip-over-perforation			No skip-over-perforation	CR command does not produce a line feed								
2-4	CR command produces a line feed			CR command does not produce a line feed	CR command produces a line feed								
2-5	8-KB buffer			1-KB buffer	1-KB buffer								
2-6	Bidirectional printing possible			Unidirectional printing only	Unidirectional printing only								
Pitch	Proportional		12 cpi	15 cpi	12 cpi	15 cpi	10 cpi	10 cpi					
2-7	ON		ON	OFF	ON	OFF	OFF	OFF					
2-8	ON		OFF	ON	ON	OFF	OFF	OFF					

Built-in features

Print method	24-pin impact		
Speed	LQ	53 cps @ 10 cpi	64 cps @ 12 cpi
	Draft	160 cps @ 10 cpi	192 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB or 1KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806242 (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165, C823032, C823021
Ribbons	#7754 (Fabric), #7770 (Film)

LQ-1010 DIP-switch settings

Country (1-7 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-7 ON)		PC437	PC850	PC860	PC863	PC865				
1-1	ON	ON	ON	ON	ON	OFF				
1-2	ON	ON	ON	OFF	OFF	ON				
1-3	ON	OFF	ON	ON	OFF	ON				
Paper length		11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches				
1-4	ON	ON	ON	OFF	OFF	OFF				
1-5	ON	OFF	ON	ON	ON	OFF				
1-6		ON Condensed printing			OFF Noncondensed printing					
1-7		Graphics character tables			Italics character table					
1-8		Cut-sheet feeder mode on			Cut-sheet feeder mode off					
2-1		Not used			Not used					
2-2		Automatic tear-off			No automatic tear-off					
2-3		1-inch skip-over-perforation			No skip-over-perforation					
2-4		CR command produces a line feed			CR command does not produce a line feed					
2-5		8-KB buffer			1-KB buffer					
2-6		Bidirectional printing possible			Unidirectional printing only					
Pitch		Proportional	12 cpi	15 cpi	15 cpi	10 cpi				
2-7		ON	ON	OFF	OFF	OFF				
2-8		ON	OFF	ON	ON	OFF				

Built-in features

Print method	24-pin impact				
Speed	LQ	73 cps @ 10 cpi	88 cps @ 12 cpi		
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi		
Print width	13.6 inches				
Paper types	Continuous, Single sheets				
Multipart forms	Original plus 3 copies				
Paper paths	Rear, Top				
Tractor	Push				
Paper parking	Available				
Buffer size	6KB				
Interfaces	Parallel, Serial				
Fonts (typefaces)	Roman, Sans Serif				

Options (with model numbers)

Cut-sheet feeders	#7340 (Single-bin), #7348 (Double-bin)
Tractor	#7312 (Pull)
Interfaces	#8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M)
Ribbons	#7754 (Fabric), #7770 (Film)
Font cartridge	#7407

LQ-1050 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
						ON	OFF			
1-4	Graphics character table			Italics character table						
1-5	Unidirectional printing only			Bidirectional printing possible						
1-6	Not used			Not used						
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off						
1-8	No buffer			6-KB buffer						
2-1	12-inch page length			11-inch page length						
2-2	1-inch skip-over perforation			No skip-over-perforation						
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel <td data-kind="ghost"></td> <td data-kind="ghost"></td> <td data-kind="ghost"></td> <td data-kind="ghost"></td>						
2-3	ON	ON	OFF	OFF						
2-4	ON	OFF	ON	OFF						
Baud	300	4,800	1,200	9,600						
2-5	ON	ON	OFF	OFF						
2-6	ON	OFF	ON	OFF						
		ON	OFF							
2-7	Automatic tear-off			No automatic tear-off						
2-8	CR command produces a line feed			CR command does not produce a line feed						

Built-in features

Print method	24-pin impact	
Speed	LQ 82 cps @ 10 cpi Draft 246 cps @ 10 cpi High-speed draft	98 cps @ 12 cpi 295 cps @ 12 cpi 300 cps @ 10 cpi
Print width	13.6 inches	
Paper types	Continuous, Single sheets, Envelopes, Labels	
Multipart forms	Original plus 3 copies	
Paper paths	Rear, Top	
Tractor	Push	
Paper parking	Available	
Buffer size	6KB	
Interfaces	Parallel, Serial	
Fonts (typefaces)	Roman, Sans Serif, Courier*, Prestige*, Script*, OCR B*, OCR A*, Orator*, Orator S*	

Options (with model numbers)

Cut-sheet feeders	#7340 (Single-bin), #7348 (Double-bin)
Tractor	#7312 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7754 (Fabric), #7770 (Film)
Font cartridge	#7407**

*Built-in from 1991 on. **Discontinued from 1991 on.

LQ-1050 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865						
1-1	ON	ON	ON	ON	OFF						
1-2	ON	ON	OFF	OFF	OFF						
1-3	ON	OFF	ON	OFF	OFF						
1-4	ON			OFF							
1-4	Graphics character tables			Italics character table							
1-5	Bidirectional printing possible			Unidirectional printing only							
1-6	Normal-speed draft			High-speed draft							
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off							
1-8	1-inch skip-over-perforation			No skip-over-perforation							
Paper length	11.7 inches	12 inches	8.5 inches	12 inches	8.5 inches	11 inches					
2-1	ON	ON	OFF	ON	OFF	OFF					
2-2	ON	OFF	ON	ON	ON	OFF					
Interface	Serial (none)	Serial (even)	Serial (odd)	Serial (odd)	Serial (odd)	Parallel					
2-3	ON	ON	OFF	OFF	OFF	OFF					
2-4	ON	OFF	ON	ON	ON	OFF					
Baud	300	19,200	1,200	1,200	1,200	9,600					
2-5	ON	ON	OFF	OFF	OFF	OFF					
2-6	ON	OFF	ON	ON	ON	OFF					
2-7	ON			OFF							
2-7	Automatic tear-off			No automatic tear-off							
2-8	CR command produces a line feed			CR command does not produce a line feed							

Built-in features

Print method	24-pin impact		
Speed	LQ	82 cps @ 10 cpi	98 cps @ 12 cpi
	Draft	246 cps @ 10 cpi	295 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	#7340 (Single-bin), #7348 (Double-bin)
Tractor	#7312 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7754 (Fabric), #7770 (Film)
Font cartridge	#7407

LQ-1050+ DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
						ON	OFF			
1-4	Graphics character table				Italics character table					
1-5	Unidirectional printing only				Bidirectional printing possible					
1-6	Normal draft				High-speed draft					
1-7	Cut-sheet feeder mode on				Cut-sheet feeder mode off					
1-8	No buffer				6-KB buffer					
2-1	12-inch page length				11-inch page length					
2-2	1-inch skip-over perforation				No skip-over-perforation					
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel						
2-3	ON	ON	OFF	OFF						
2-4	ON	OFF	ON	OFF						
Baud	300	19,200	1,200	9,600						
2-5	ON	ON	OFF	OFF						
2-6	ON	OFF	ON	OFF						
		ON	OFF							
2-7	Automatic tear-off				No automatic tear-off					
2-8	CR command produces a line feed				CR command does not produce a line feed					

Built-in features

Print method	24-pin impact		
Speed	LQ	75 cps @ 10 cpi	90 cps @ 12 cpi
	Draft	225 cps @ 10 cpi	270 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	6KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	C806181 (Single-bin), C806191 (Double-bin)
Tractor	C800101 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ribbons	#7762 (Fabric), #7764 (Film), #7763 (Color)
Font cartridge	#7407

LQ-1060 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
ON						OFF					
1-4	Graphics character table				Italics character table						
1-5	Unidirectional printing only				Bidirectional printing possible						
1-6	Normal-speed draft				High-speed draft						
1-7	Cut-sheet feeder mode on				Cut-sheet feeder mode off						
1-8	No buffer				6-KB buffer						
2-1	12-inch page length				11-inch page length						
2-2	1-inch skip-over perforation				No skip-over-perforation						
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel							
2-3	ON	ON	OFF	OFF							
2-4	ON	OFF	ON	OFF							
Baud	300	19,200	1,200	9,600							
2-5	ON	ON	OFF	OFF							
2-6	ON	OFF	ON	OFF							
ON						OFF					
2-7	Automatic tear-off				No automatic tear-off						
2-8	CR command produces a line feed				CR command does not produce a line feed						

Built-in features

Print method	24-pin impact
Speed	LQ 82 cps @ 10 cpi 98 cps @ 12 cpi Draft 246 cps @ 10 cpi 295 cps @ 12 cpi High-speed draft 300 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	6KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif

Options (with model numbers)

Cut-sheet feeders	C806181 (Single-bin), C806191 (Double-bin)
Tractor	C800101 (Pull) #8143, #8148, #8165, #8641, #8642
Interfaces	#7762 (Fabric), #7764 (Film), #7763 (Color)
Ribbons	
Font cartridge	#7407

LQ-1060 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865						
1-1	ON	ON	ON	ON	OFF						
1-2	ON	ON	OFF	OFF	OFF						
1-3	ON	OFF	ON	ON	OFF						
	ON			OFF							
1-4	Graphics character tables			Italics character table							
1-5	Unidirectional printing only			Bidirectional printing possible							
1-6	Normal-speed draft			High-speed draft							
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off							
1-8	1-inch skip-over-perforation			No skip-over-perforation							
Paper length	11.7 inches	12 inches	8.5 inches	8.5 inches	8.5 inches	11 inches	11 inches	11 inches			
2-1	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF			
2-2	ON	OFF	ON	ON	ON	ON	ON	ON			
Interface	Serial (none)	Serial (even)	Serial (odd)	Serial (odd)	Serial (odd)	Parallel	Parallel	Parallel			
2-3	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF			
2-4	ON	OFF	ON	ON	ON	ON	ON	ON			
Baud	300	19,200	1,200	1,200	1,200	9,600	9,600	9,600			
2-5	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF			
2-6	ON	OFF	ON	ON	ON	ON	ON	ON			
	ON			OFF							
2-7	Automatic tear-off			No automatic tear-off							
2-8	CR command produces a line feed			CR command does not produce a line feed							

Built-in features

Print method	24-pin impact
Speed	LQ 82 cps @ 10 cpi 98 cps @ 12 cpi Draft 246 cps @ 10 cpi 295 cps @ 12 cpi High-speed draft 300 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	6KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif

Options (with model numbers)

Cut-sheet feeders	C806181 (Single-bin), C806191 (Double-bin)
Tractor	C800101 (Pull) #8143, #8148, #8165, #8641, #8642
Interfaces	#7762 (Fabric), #7764 (Film), #7763 (Color)
Ribbons	
Font cartridge	#7407

LQ-1060+ DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865						
1-1	ON	ON	ON	ON	OFF						
1-2	ON	ON	OFF	OFF	OFF						
1-3	ON	OFF	ON	ON	OFF						
	ON			OFF							
1-4	Graphics character tables			Italics character table							
1-5	Unidirectional printing only			Bidirectional printing possible							
1-6	Normal-speed draft			High-speed draft							
1-7	Cut-sheet feeder mode on			Cut-sheet feeder mode off							
1-8	1-inch skip-over-perforation			No skip-over-perforation							
Paper length	11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches						
2-1	ON	ON	OFF	OFF	OFF						
2-2	ON	OFF	ON	ON	OFF						
Interface	Serial (none)	Serial (even)	Serial (odd)	Serial (odd)	Parallel						
2-3	ON	ON	OFF	OFF	OFF						
2-4	ON	OFF	ON	ON	OFF						
Baud	300	19,200	1,200	1,200	9,600						
2-5	ON	ON	OFF	OFF	OFF						
2-6	ON	OFF	ON	ON	OFF						
	ON			OFF							
2-7	Automatic tear-off			No automatic tear-off							
2-8	CR command produces a line feed			CR command does not produce a line feed							

Built-in features

Print method	24-pin impact
Speed	LQ 70 cps @ 10 cpi 84 cps @ 12 cpi Draft 210 cps @ 10 cpi 252 cps @ 12 cpi High-speed draft 225 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top, Bottom, Front
Tractors	Push, Pull
Paper parking	Available
Buffer size	8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C

Options (with model numbers)

Cut-sheet feeders	C80639*, C80640* (Single-bin)
Tractor	C80022* (Pull)
Interfaces	C82305*, C82306*, C82307*, C82308*
Ribbons	#7754 (Fabric), #7770 (Film)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-1070 DIP-switch setting

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865					
1-1	ON	ON	ON	ON	OFF					
1-2	ON	ON	OFF	OFF	OFF					
1-3	ON	OFF	ON	ON	OFF					
1-4	ON			OFF						
1-5	Graphics character tables			Italics character table						
1-6	Unidirectional printing only			Bidirectional printing possible						
1-7	High-speed draft printing			Normal draft printing						
1-8	No buffer			8-KB buffer						
Paper length	11.7 inches	12 inches	8.5 inches	8.5 inches	11 inches					
2-1	ON	ON	OFF	OFF	OFF					
2-2	ON	OFF	ON	ON	OFF					
2-3	ON			OFF						
2-4	Automatic tear-off			No automatic tear-off						
	CR command produces a line feed			CR command does not produce a line feed						

Year introduced: 1993
Market: America, Europe, Pacific

Built-in features

Print method	24-pin impact		
Speed	LQ	75 cps @ 10 cpi	90 cps @ 12 cpi
	Draft	225 cps @ 10 cpi	269 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top, Bottom, Front		
Tractors	Push, Pull		
Paper parking	Available		
Buffer size	0, 8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C, Roman T, Sans Serif H		
Nonprintable area	5.3 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	C80639* (Single-bin), C80640* (High-capacity)		
Tractor	C80022* (Pull)		
Interfaces	C82305*, C82306*, C82307*, C82308*, C82310*, C82311*, C82313*		
Ribbons	#7754 (Fabric), #7770 (Film)		

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-1070+ DIP-switch setting

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark I	Sweden	Italy	Spain I
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-4 ON)	PC437	PC850	PC860	PC863	PC865	BRASCI* PC437**	Abicomp* PC853**	PC437* PC852**
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF

*These character tables are not available on the European version.

**These character tables are available only on the European version.

	ON	OFF
1-4	Graphics character tables	Italics character table
1-5	Unidirectional printing only	Bidirectional printing possible
1-6	IBM emulation*	ESC/P 2
1-7	No buffer	8-KB buffer
1-8	1-inch skip-over-perforation	No skip-over-perforation

*DIP switch 1-6 functions only on the European version of this printer.

Paper length	11.7 inches	12 inches	8.5 inches	11 inches
2-1	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF

	ON	OFF
2-3	Automatic tear-off	No automatic tear-off
2-4	Auto line feed	No auto line feed

DIP-switch settings for IBM emulation mode

Character table (1-6 ON)	437	850	860	863	865	437 Greek	853	852
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
1-4	Character set 1	Character set 2
1-8	Alternate graphics mode on*	Alternate graphics mode off
2-1	12-inch page length (cont. paper)	11-inch page length (cont. paper)
2-2	Auto CR enabled	Auto CR disabled

*With DIP-switch 1-8 ON, ESC 3, ESC A, ESC J, and ESC * function the same as in ESC/P.

Year introduced: 1991
Market: America, Europe, Pacific

Built-in features

Print method	24-pin impact		
Speed	LQ	73 cps @ 10 cpi	88 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
	High-speed draft		300 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top, Bottom, Front		
Tractors	Push, Pull		
Paper parking	Available		
Buffer size	64KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C		

Options (with model numbers)

Cut-sheet feeders	C80639*, C80640* (Single-bin)
Tractor	C80021* (Pull)
Interfaces	C82305*, C82306*, C82307*, C82308*
Ribbons	#7754 (Fabric), #7770 (Film)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-1170 DIP-switch setting

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain									
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF									
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF									
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF									
Character table (1-4 ON)			PC437	PC850	PC860	PC863	PC865										
1-1	ON		ON		ON	ON	OFF										
1-2	ON		ON		OFF	OFF	ON										
1-3	ON		OFF		ON	OFF	ON										
		ON			OFF												
1-4	Graphics character tables			Italics character table													
1-5	Unidirectional printing only			Bidirectional printing possible													
1-6	High-speed draft printing			Normal draft printing													
1-7	No buffer			64-KB buffer													
1-8	1-inch skip-over-perforation			No skip-over-perforation													
Paper length		11.7 inches	12 inches	8.5 inches	11 inches												
2-1	ON		ON		OFF	OFF											
2-2	ON		OFF		ON	OFF											
		ON			OFF												
2-3	Automatic tear-off			No automatic tear-off													
2-4	CR command produces a line feed			CR command does not produce a line feed													

Built-in features

Print method	24-pin impact
Speed	LQ 67 cps @ 10 cpi Draft 200 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	2KB
Interface	Parallel
Font (typeface)	Roman
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8344 (Double-bin)
Tractor	#8303 (Pull)
Interfaces	#8148, #8165, #8172
Ribbon	#8753 (Fabric)

LQ-1500 DIP-switch settings

	ON					OFF			
1-1	No buffer					2-KB buffer			
1-2	Paper-end sensor off					Paper-end sensor on			
1-3	CR command produces a line feed					CR command does not produce a line feed			
1-4	Not used					Not used			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain	
2-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF	
2-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF	
2-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF	
	ON					OFF			
2-4	12-inch page length					11-inch page length			
2-5	1-inch skip-over-perforation					No skip-over-perforation			
2-6	Bell disabled					Bell available			
2-7	LQ printing					Draft printing			
2-8	Receive SLCT IN signal					SLCT IN signal ignored			

Built-in features

Print method	24-pin impact
Speed	LQ 92 cps @ 10 cpi 110 cps @ 12 cpi Draft 275 cps @ 10 cpi 330 cps @ 12 cpi High-speed draft 300 cpi @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels, Cards, Roll paper
Multipart forms	Original plus 3 copies
Paper paths	Front, Rear, Bottom In, Top Out
Tractors	Push, Pull
Paper parking	Available
Buffer size	0, 64KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C, Roman T, Sans Serif H
Bar codes	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Nonprintable area	4.2 mm at the top and bottom of single sheets

Options (with model numbers)

Cut-sheet feeders	C80673* (High-capacity), C80674* (Second-bin)
Pull tractor unit	C80032*
Roll paper holder	#8310
Interfaces	C82305*, C82306*, C82307*, C82308*, C82310*, C82311*, C82312*, C82313*, C82314*, C82315*, C82331*
Ribbons	S015083/S015086 (Cartridge), S010031/S010033 (Pack)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-2070 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Page length for front tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Page length for rear tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Skip-over-perforation	On or Off
Auto tear off	On or Off
Auto line feed	On or Off
Print direction	Auto, Bi-d or Uni-d
I/F mode	Auto, Parallel, or Option
Auto I/F wait time	10 or 30 sec.
Software	ESC/P 2 or IBM 2391 Plus
Character table	Italic, PC437, PC437 Greek*, PC774*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC864*, PC865, PC866*, PC866 LAT*, PC869*, BRASCI, Abicomp, Roman 8, ISO Latin 1, ISO 8859-2*, MAZOWIA*, Code MJK*, ISO 8859-7*, ISO Latin 1T*, Bulgaria*, Estonia*
International character set	U.S.A., France, Germany, U.K., Denmark 1, Sweden, Italy, Spain 1
0 slash	0 or Ø
High speed draft	On or Off
Input buffer	On or Off
Buzzer	On or Off
Auto CR	On or Off †
A.G.M.	On or Off †
Font	OCR-B, Orator, Orator-S, Script C, Roman T (PS), Sans Serif H (PS)
Roll paper	On or Off

* Availability varies by country.

† This setting is available only in IBM mode.

Built-in features

Print method	24-pin impact
Speed	LQ 73 cps @ 10 cpi 88 cps @ 12 cpi Draft 220 cps @ 10 cpi 264 cps @ 12 cpi High-speed draft 300 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels, Cards, Roll paper
Multipart forms	Original plus 4 copies
Paper paths	Front, Rear, Bottom In, Top Out
Tractors	Push, Pull
Paper parking	Available
Buffer size	0 or 64KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, Orator, Orator S, Script C, Roman T, Sans Serif H
Bar codes	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Nonprintable area	4.2 mm at the top and bottom of single sheets

Options (with model numbers)

Cut-sheet feeders	C80673* (High-capacity), C80674* (Second-bin)
Pull tractor unit	C80032*
Roll paper holder	#8310
Interfaces	C82305*, C82306*, C82307*, C82308*, C82310*, C82311*, C82312*, C82313*, C82314*, C82315*, C82331*
Ribbons	S015083 (Cartridge), S010031 (Pack)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LQ-2170 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Page length for front tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Page length for rear tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Skip-over-perforation	On or Off
Auto tear off	On or Off
Auto line feed	On or Off
Print direction	Auto, Bi-d or Uni-d
I/F mode	Auto, Parallel, or Option
Auto I/F wait time	10 or 30 sec.
Software	ESC/P 2 or IBM 2391 Plus
Character table	Italic, PC437, PC437 Greek*, PC774*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC864*, PC865, PC866*, PC866 LAT*, PC869*, BRASCI, Abicomp, Roman 8, ISO Latin 1, ISO 8859-2*, MAZOWIA*, Code MJK*, ISO 8859-7*, ISO Latin 1T*, Bulgaria*, Estonia*
International character set	U.S.A., France, Germany, U.K., Denmark 1, Sweden, Italy, Spain 1
0 slash	0 or Ø
High speed draft	On or Off
Input buffer	On or Off
Buzzer	On or Off
Auto CR	On or Off †
A.G.M.	On or Off †
Font	OCR-B, Orator, Orator-S, Script C, Roman T (PS), Sans Serif H (PS)
Roll paper	On or Off

* Availability varies by country.

† This setting is available only in IBM mode.

Built-in features

Print method	24-pin impact		
Speed	LQ	90 cps @ 10 cpi	108 cps @ 12 cpi
	Draft	270 cps @ 10 cpi	324 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 4 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, SerialFonts (typefaces) Roman, Sans Serif, Courier, Prestige, Script		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	#8343 (Single-bin), #8346 (Double-bin)
Tractor	#8303 (Pull)
Interfaces	#8131, #8132(W), #8133, #8143, #8145, #8148, #8149, #8149M, #8161, #8165, #8172, #8172M
Ribbons	#7756 (Fabric), #7768 (Film), #7757 (Color)
Color kit	#8391E
Font cartridge	#7404
Image scanner kit	#7392J

Note:

The LQ-2500 has no DIP switches.

Built-in features

Print method	24-pin impact		
Speed	LQ	90 cps @ 10 cpi	108 cps @ 12 cpi
	Draft	270 cps @ 10 cpi	324 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 4 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	#8343 (Single-bin), #8346 (Double-bin)
Tractor	#8308 (Pull)
Interfaces	#8131, #8132(W), #8133, #8143, #8145, #8148, #8149, #8149M, #8161, #8165, #8172, #8172M
Ribbons	#7756 (Fabric), #7768 (Film), #7757 (Color)
Color kit	#8391E
Font cartridge	#7404

Note:

The LQ-2500+ has no DIP switches.

Built-in features

Print method	24-pin impact		
Speed	LQ	111 cps @ 10 cpi	133 cps @ 12 cpi
	Draft	333 cps @ 10 cpi	400 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 5 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A		

Options (with model numbers)

Cut-sheet feeder	#7343 (Double-bin)
Tractor	#7314 (Pull)
Interfaces	#8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M), #8133, #8172, #8172M
Ribbons	#7762 (Fabric), #7764 (Film), #7763 (Color)
Font cartridge	#7407

Note:

The LQ-2550 has no DIP switches.

Built-in features

Print method	24-element thermal
Print width	8 inches
Paper types	Single sheets, Roll paper (thermal)
Paper path	Top
Paper parking	Not available
Interface	Serial (6-pin DIN connector)
Font (typeface)	Roman
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Ribbons	#8760 (Film, thermal)
---------	-----------------------

P-80X DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
1-4	CR command produces a line feed	CR command does not produce a line feed
2-1	7-bit data length	8-bit data length
2-2	Parity checked	No parity check
2-3	Even parity	Odd parity
2-4	1 stop bit	2 stop bits

bps	75	1,800	200	300	134.5	4,800	600	2,400	110	2,400	300	1,200	150	9,600	1,200	9,600
2-5	ON	ON	ON	ON	ON	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
2-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF	ON	OFF	ON	OFF	ON	OFF	ON	OFF

Built-in features

Print method	24-nozzle ink jet
Speed	LQ 165 cps @ 10 cpi 198 cps @ 12 cpi Draft 450 cps @ 10 cpi 540 cps @ 12 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	8KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script

Options (with model numbers)

Cut-sheet feeders	C806081 (Single-bin), C806091 (Double-bin)
Tractor	C800032 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ink cartridge	S020002

Note:

The SQ-850 has no DIP switches.

Built-in features

Print method	24-nozzle ink jet		
Speed	LQ	165 cps @ 10 cpi	198 cps @ 12 cpi
	Draft	500 cps @ 10 cpi	600 cps @ 12 cpi
		8 inches	Print width
Paper types	Continuous, Single sheets, Envelopes, Labels		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeders	C806081 (Single-bin), C806091 (Double-bin)
Tractor	C800032 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ink cartridge	S020002

Note:

The SQ-850 has no DIP switches.

Built-in features

Print method	48-nozzle ink jet		
Speed	LQ	200 cps @ 10 cpi	240 cps @ 12 cpi
	Draft	550 cps @ 10 cpi	660 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Paper paths	Rear, Top, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	16KB or 128KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, Orator, Orator S, Script C		

Options (with model numbers)

Cut-sheet feeders	C806481 (Single-bin), C806372 (High-capacity)		
Tractor	C800241 (Pull)		
Roll-paper holder	N/A		
Interfaces	C823061, C823081, C823102, C823132		
Ink cartridge	S020010		

SQ-870 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-4 ON)	PC437			PC850			PC860			
1-1	ON			ON			ON			
1-2	ON			ON			OFF			
1-3	ON			OFF			ON			
1-4	ON			OFF			Graphics character tables			
1-5	Unidirectional printing only			Italics character table			Bidirectional printing possible			
1-6	Not used			Not used						
1-7	Not used			Not used						
1-8	Not used			Not used						
Paper length	11.7 inches		12 inches		8.5 inches		11 inches			
2-1	ON		ON		OFF		OFF			
2-2	ON		OFF		ON		OFF			
2-3	ON			OFF			1-inch skip-over-perforation			
2-4	CR command produces a line feed			No skip-over perforation			CR command does not produce a line feed			

Built-in features

Print method	48-nozzle ink jet		
Speed	LQ	200 cps @ 10 cpi	240 cps @ 12 cpi
	Draft	550 cps @ 10 cpi	660 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Paper paths	Rear, Top, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	16KB or 128KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, Orator, Orator S, Script C		

Options (with model numbers)

Cut-sheet feeders	C806471 (Single-bin), C806392 (High-capacity)		
Tractor	C800231 (Pull)		
Roll-paper holder	N/A		
Interfaces	C823061, C823081, C823132, C823132		
Ink cartridge	S020010		

SQ-1170 DIP-switch settings

Country (1-4 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
Character table (1-4 ON)	PC437			PC850			PC860			
1-1	ON	ON			ON	ON				
1-2	ON	ON			OFF	OFF				
1-3	ON	OFF			ON	OFF				
1-4	ON			OFF			Graphics character tables			
1-5	Not used			Not used			Italics character table			
1-6	Not used			Not used			Not used			
1-7	Not used			Not used			Not used			
1-8	1-inch skip-over-perforation			No skip-over-perforation						
Paper length	11.7 inches		12 inches		8.5 inches		11 inches			
2-1	ON	ON		OFF		OFF				
2-2	ON	OFF		ON		OFF				
2-3	ON			OFF			1-inch skip-over-perforation			
2-4	CR command produces a line feed			No skip-over perforation			CR command does not produce a line feed			

Built-in features

Print method	24-nozzle ink jet		
Speed	LQ	105 cps @ 10 cpi	105 cps @ 12 cpi
	Draft	176 cps @ 10 cpi	211 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Paper paths	Rear, Top		
Paper parking	Not available		
Interface	Parallel		
Fonts (typefaces)	N/A		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	#8335 (Single-bin), #8345 (Double-bin)
Tractor	#8302 (Pull)
Interfaces	#8148, #8165, #8172
Ink cartridge	#7750

SQ-2000 DIP-switch settings

Columns	136	109	102	94	80	78	75	65
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
1-4	ON				OFF			
	Cut-sheet feeder mode					No cut-sheet feeder		
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
2-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
2-4	ON 12-inch page length				OFF 11-inch page length			
2-5	1-inch skip-over-perforation				No skip-over-perforation			
2-6	Bell disabled				Bell available			
2-7	LQ printing				Draft printing			
2-8	Receive <u>SLCT IN</u> signal				<u>SLCT IN</u> signal ignored			

Built-in features

Print method	24-nozzle ink jet		
Speed	LQ	165 cps @ 10 cpi	198 cps @ 12 cpi
	Draft	450 cps @ 10 cpi	540 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Labels		
Paper paths	Rear, Top		
Paper parking	Not available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	#7342 (Single-bin), #7336 (Double-bin)
Tractor	#7305 (Pull)
Interfaces	#8145, #8148, #8149, #8149M, #8161, #8165, #8172, #8172M
Ink cartridge	#7760

Note:

The SQ-2500 has no DIP switches.

Built-in features

Print method	24-nozzle ink jet		
Speed	LQ	165 cps @ 10 cpi	198 cps @ 12 cpi
	Draft	450 cps @ 10 cpi	540 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script		

Options (with model numbers)

Cut-sheet feeders	C806101 (Single-bin), C806111 (Double-bin)
Tractor	C800042 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ink cartridge	S020002

Note:

The SQ-2550 has no DIP switches.

Built-in features

Print method	24-nozzle ink jet
Speed	LQ 165 cps @ 10 cpi 198 cps @ 12 cpi
Draft	500 cps @ 10 cpi 600 cps @ 12 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets, Envelopes, Labels
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	8KB
Interfaces	Parallel, Serial
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S

Options (with model numbers)

Cut-sheet feeders	C806101 (Single-bin), C806111 (Double-bin)
Tractor	C800042 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ink cartridge	S020002

Note:

The SQ-2550 has no DIP switches.

Built-in features

Print method	48-nozzle ink jet	
Speed	LQ 110 cps @ 10 cpi 132 cps @ 12 cpi	
Print width	8 inches	
Paper types	Single sheets, Envelopes	
Paper paths	Top, Front	
Buffer size	24KB or 8KB	
Interface	Parallel	
Fonts (typefaces)	Roman, Sans Serif, Roman T, Sans Serif H, Courier, Prestige, Script	
Nonprintable area	3.0 mm or 8.5 mm at the top of single sheets (Selectable)	

Options (with model numbers)

Ink cartridge	S020031
---------------	---------

Stylus 300 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC863, PC865, PC866*, BRASCI, Abicomp
Auto print direction	On or Off
Auto line feed	On or Off
Network interface mode	On or Off
Mixed text / graphics mode	On or Off
Loading position	3 mm or 8.5 mm

* Availability varies by country.

Stylus 400

Year introduced: 1994
Market: America, Europe, Pacific

Built-in features

Print method	48-nozzle ink jet		
Speed	LQ	120 cps @ 10 cpi	144 cps @ 12 cpi
Print width	8 inches		
Paper types	Single sheets, Envelopes		
Paper paths	Top, Front		
Buffer size	24KB or 8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Roman T, Sans Serif H, Courier, Prestige		
Nonprintable area	3.0 mm or 8.5 mm at the top of single sheets (Selectable)		

Options (with model numbers)

Ink cartridge	S020025
---------------	---------

Stylus 400 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC863, PC865, PC866*, PC869*, ISO 8859-7*, ISO Latin 1T*, MAZOWIA*, Code MJK*, Bulgaria*, BRASCI, Abicomp
Auto print direction	On or Off
Auto line feed	On or Off
Network interface mode	On or Off
Mixed text / graphics mode	On or Off
Loading position	3 mm or 8.5 mm

* Availability varies by country.

*Year introduced: 1993
Market: America, Europe, Pacific*

Built-in features

Print method	48-nozzle ink jet
Speed	LQ 150 cps @ 10 cpi 180 cps @ 12 cpi
Print width	8 inches
Paper types	Single sheets, Envelopes
Paper paths	Top, Front
Buffer size	32KB or 8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif, Roman T, Sans Serif H, Courier, Prestige, Script
Nonprintable area	3.0 mm at the top of single sheets

Options (with model numbers)

Ink cartridge S020025

Stylus 800 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC863, PC865, PC866*, BRASCI, Abicomp
Auto print direction	On or Off
Auto line feed	On or Off
Network interface mode	On or Off
Mixed text / graphics mode	On or Off

* Availability varies by country.

Built-in features

Print method	48-nozzle ink jet		
Speed	LQ	165 cps @ 10 cpi	198 cps @ 12 cpi
	Draft	250 cps @ 10 cpi	300 cps @ 12 cpi
Print width	8 inches		
Paper types	Single sheets, Envelopes		
Paper paths	Top, Front		
Buffer size	32KB or 8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Roman T, Sans Serif H, Courier, Prestige, Script		
Nonprintable area	3.0 mm at the top of single sheets		

Options (with model numbers)

Ink cartridge	S020025
---------------	---------

Stylus 800+ default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC852*, PC853*, PC855*, PC857*, PC860*, PC863*, PC865*, PC866*, BRASCII*, Abicomp*, MAZOWIA*, Code MJK*, ISO 8859-7, ISO Latin 1T*, Bulgaria*
Auto print direction	On or Off
Network interface mode	On or Off
Mixed text / graphics mode	On or Off
Auto line feed	On or Off

* Availability varies by country.

Stylus 1000

Year introduced: 1993
Market: America, Europe, Pacific

Built-in features

Print method	48-nozzle ink jet		
Speed	LQ	150 cps @ 10 cpi	180 cps @ 12 cpi
	Draft	250 cps @ 10 cpi	300 cps @ 12 cpi
Print width	8 inches		
Paper types	Single sheets, Envelopes		
Paper paths	Top, Front		
Buffer size	64KB or 128KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif, Roman T, Sans Serif H, Courier, Prestige, Script		
Nonprintable area	3.0 mm at the top of single sheets		

Options (with model numbers)

Interfaces	C82305*/C82306*, C82307*/C82308*, C82310*, C82313*, C82312*
Push-tractor	C80029*
Ink cartridge	S020025

*The last digit of the option model numbers shown above as an asterisk varies by country.

Stylus 1000 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC863, PC865, PC866*, BRASCI**, Abicomp**
Auto print direction	On or Off
Continuous-paper page length	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Network interface mode	On or Off
Mixed text / graphics mode	On or Off
Auto line feed	On or Off
Auto interface selection	On or Off
Auto interface wait time	30 sec. or 10 sec.
Tear off	On or Off

* Available only in European versions.

** Available only in the American version.

Built-in features

Print method	64-nozzle ink jet (Black)
Speed	48-nozzle ink jet (Cyan, Magenta, Yellow)
Print width	LQ 200 cps @ 10 cpi 240 cps @ 12 cpi
Paper types	8 inches
Paper path	Single sheets, Envelopes, Transparencies
Buffer size	Front
Interfaces	64KB
Fonts (typefaces)	Parallel, Serial, Option
Nonprintable area	Roman, Sans Serif, Roman T, Sans Serif H, Courier, Prestige, Script
	3.0 mm or 8.5 mm at the top of single sheets (Selectable)

Options (with model numbers)

Ink cartridges	S020034 (Black), S020036 (Color)
----------------	----------------------------------

Stylus Color default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	Italic, PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC865, PC866*, Abicomp, BRASCI
Auto print direction	Auto, Uni-d, or Bi-d
Auto line feed	On or Off
Network interface mode	On or Off
Loading position	3 mm or 8.5 mm
Interface mode	Auto, Parallel, Serial, or Option
Auto interface wait mode	10 sec. or 30 sec.

* Availability varies by country.

Built-in features

Print method	48-pin impact		
Speed	LQ	83 cps @ 10 cpi	100 cps @ 12 cpi
	Draft	250 cps @ 10 cpi	300 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeder	C806001 (Double-bin)
Tractor	C800001 (Pull)
Interfaces	#8143, #8148, #8165
Ribbons	S015001 (Fabric), S015011 (Film)

Note:

The TLQ-4800 has no DIP switches.

Built-in features

Print method	48-nozzle ink jet		
Speed	LQ	180 cps @ 10 cpi	216 cps @ 12 cpi
	Draft	500 cps @ 10 cpi	600 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Courier, Prestige, Script, OCR B, OCR A, Orator, Orator S		

Options (with model numbers)

Cut-sheet feeders	C806101 (Single-bin), C806111 (Double-bin)
Tractor	C800042 (Pull)
Interfaces	#8143, #8148, #8165, #8641, #8642
Ink cartridge	S020002

Note:

The TLQ-4800 has no DIP switches.

9-Pin Printers

ActionPrinter Apex 80

Year introduced: 1988

Market: America

Built-in features

Print method	9-pin impact				
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi		
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi		
Print width	8 inches				
Paper types	Continuous, Single sheets, Envelopes, Roll paper				
Multipart forms	Original plus 2 copies				
Paper paths	Rear, Top				
Tractor	Pull				
Paper parking	Not available				
Buffer size	3KB				
Interface	Parallel				
Fonts (typefaces)	Roman, Sans Serif				
Nonprintable area	22.0 mm at the top of single sheets				

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165, #8172
Ribbon	#8750 (Fabric)

ActionPrinter Apex 80 DIP-switch settings

		ON				OFF				
1-1		Condensed printing				Noncondensed printing				
1-2		Slashed zero (Ø)				Normal zero (0)				
1-3		Graphics character table				Italics character table				
1-4		Paper-end sensor off				Paper-end sensor on				
1-5		Draft printing				NLQ printing				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
		ON				OFF				
2-1		12-inch page length				11-inch page length				
2-2		Cut-sheet feeder mode on				Cut-sheet feeder mode off				
2-3		1-inch skip-over-perforation				No skip-over-perforation				
2-4		CR command produces a line feed				CR command does not produce a line feed				

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8348 (Single-bin)
Interfaces	#8148, #8165, #8172
Ribbon	#8755(M) (Fabric)

ActionPrinter T-750 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	ESC/P mode: Graphics character table IBM mode: CR produces no line feed				ESC/P mode: Italics character table IBM mode: CR produces line feed			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	12-inch page length	11-inch page length
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

ActionPrinter T-1000 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	Paper-end sensor off				Paper-end sensor on			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806121 (Single-bin)
Tractor	C800061 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

ActionPrinter 2000 DIP-switch settings

	ON	OFF
1-1	12-cpi printing	10-cpi printing
1-2	Slashed zero (Ø)	Normal zero (0)
1-3	Graphics character table	Italics character table
1-4	Automatic tear-off	No automatic tear-off
1-5	Normal draft printing	High-speed draft printing

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	12-inch page length	11-inch page length
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Front		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Tractor	C800262 (Push)
Ribbon	S015047 (Fabric)

ActionPrinter 2250 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC850, PC860, PC863, PC865, BRASCII, Abicomp
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Tear-off position	On or Above tear-off edge
Top-of-form position	-3, -2, -1, ±0, 1, 2, 3
Shape of zero	Unslashed (0) or slashed (Ø) zero
Back feed	Enable or Disable
Auto line feed	On or Off
Character pitch	10 or 12 cpi

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806242 (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165
Ribbon	#8755 (Fabric)

ActionPrinter 2500 DIP-switch settings

Switch	ON				OFF			
1-1	12-cpi printing				10-cpi printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	Automatic tear-off				No automatic tear-off			
1-5	Normal draft printing				High-speed draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	80 cps @ 10 cpi	96 cps @ 12 cpi
	Draft	400 cps @ 10 cpi	480 cps @ 12 cpi
	High-speed draft		533 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Labels		
Multipart forms	Front tractor: original plus 5 copies Rear tractor: original plus 3 copies		
Paper paths	Rear, Front		
Tractors	Push (front and rear)		
Paper parking	Available		
Buffer size	3KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Tractor	#8309 (Pull)
Interfaces	#8133W, #8143, #8145, #8148, #8149, #8149M, #8165, #8641, #8642
Ribbon	#8766 (Fabric)

DFX-5000 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	No buffer				3-KB buffer			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Normal draft printing				High-speed draft printing			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			
Interface	Serial (none)		Serial (even)		Serial (odd)		Parallel	
2-5	ON		ON		OFF		OFF	
2-6	ON		OFF		ON		OFF	
Baud	300		1,200		4,800		9,600	
2-7	ON		ON		OFF		OFF	
2-8	ON		OFF		ON		OFF	

Built-in features

Print method	9-pin impact		
Speed	NLQ	84 cps @ 10 cpi	101 cps @ 12 cpi
	Draft	420 cps @ 10 cpi	504 cps @ 12 cpi
	High-speed draft		560 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Labels		
Multipart forms	Front tractor: original plus 5 copies Rear tractor: original plus 3 copies		
Paper paths	Rear, Front		
Tractors	Push (front and rear)		
Paper parking	Available		
Buffer size	20KB, 0KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Tractor	#8309 (Pull)
Interfaces	C82305*/C82306*, C82307*/C82308*, C82310*, C82312*, C82313*, C82314*, C82315*, C82324*
Ribbon	#8766 (Fabric)

*The last digit of the option number shown above as an asterisk varies by country.

Not all interfaces are available in all countries.

DFX-5000+ DIP-switch settings

	ON	OFF
1-1	IBM ProPrinter II emulation mode	EPSON ESC/P mode
1-2	Normal printing	High-speed printing
1-3	NLQ printing	Draft printing
1-4-8	Character table (ESC/P mode)	See table A
1-4-8	Function settings (IBM mode)	See table B
	ON	OFF
2-1	Slashed zero (Ø)	Normal zero (0)
2-2	No buffer	20-KB buffer
2-3 †	Auto line feed on	Auto line feed off
Auto interface selection	Odd parity for serial (wait time: 30 sec.)	Odd parity for serial (wait time: 10 sec.)
2-4	OFF	OFF
2-5	OFF	ON
2-6	OFF	ON
Interface	Serial (none)	Serial (even)
2-4	ON	ON
2-5	ON	OFF
2-6	ON	ON
Baud	300	1,200
2-7	ON	ON
2-8	ON	OFF
Page length	11 inches	12 inches
3-1	OFF	ON
3-2	OFF	ON

† This setting is available only in IBM mode.

DFX-5000+ DIP-switch settings (continued)

	ON	OFF
3-3	Skip-over-perforation on	Skip-over-perforation off
3-4	Paper memory setting 2	Paper memory setting 1
3-5	Overlapping multipart forms printing enabled	Overlapping multipart forms printing disabled
3-6	Multipart forms with labels printing enabled	Multipart forms with labels printing disabled
3-7	Skip over binding on	Skip over binding off
3-8	Automatic tear off enabled	Automatic tear off disabled

Table A (EPSON ESC/P mode only)

Character table	1-4	1-5	1-6	1-7	1-8
Italic U.S.A.	OFF	OFF	OFF	OFF	OFF
Italic France	OFF	OFF	OFF	OFF	ON
Italic Germany	OFF	OFF	OFF	ON	OFF
Italic U.K.	OFF	OFF	OFF	ON	ON
Italic Denmark	OFF	OFF	ON	OFF	OFF
Italic Sweden	OFF	OFF	ON	OFF	ON
Italic Italy	OFF	OFF	ON	ON	OFF
Italic Spain	OFF	OFF	ON	ON	ON
PC437	OFF	ON	OFF	OFF	OFF
PC850	OFF	ON	OFF	OFF	ON
PC860	OFF	ON	OFF	ON	OFF
PC863	OFF	ON	OFF	ON	ON
PC865	OFF	ON	ON	OFF	OFF
PC861	OFF	ON	ON	OFF	ON
BRASCI	OFF	ON	ON	ON	OFF
Abicomp	OFF	ON	ON	ON	ON
PC437 Greek*	ON	OFF	OFF	OFF	OFF
PC869*	ON	OFF	OFF	OFF	ON
ISO 8859-7*	ON	OFF	OFF	ON	OFF
PC853*	ON	OFF	OFF	ON	ON
PC857*	ON	OFF	ON	OFF	OFF
ISO Latin 1T*	ON	OFF	ON	OFF	ON
PC855*	ON	OFF	ON	ON	OFF
PC866*	ON	OFF	ON	ON	ON
PC852*	ON	ON	OFF	OFF	OFF
MAZOWIA*	ON	ON	OFF	OFF	ON
Code MJK*	ON	ON	OFF	ON	OFF
Bulgaria	ON	ON	OFF	ON	ON

Table B (IBM ProPrinter emulation mode)

	ON	OFF
1-4	Auto carriage return enabled	Auto carriage return disabled
1-5	—	—
1-6	80-9FH characters printed	80-9FH commands
1-7	—	—
1-8	PC865 character table selected	PC437 character table selected

Built-in features

Print method	9-pin impact		
Speed	NLQ	160 cps @ 10 cpi	192 cps @ 12 cpi
	Draft	800 cps @ 10 cpi	960 cps @ 12 cpi
	High-speed draft		1066 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Labels		
Multipart forms	Front tractor: original plus 5 copies; Rear tractor: original plus 3 copies		
Paper paths	Rear, Front		
Tractors	Push (front and rear)		
Paper parking	Available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Tractor	#8309 (Pull)
Paper cutter	C81500*
Interfaces	#8143, #8148, #8165, #8641, #8142
Ribbon	#8766 (Fabric)

*The last digit of the option model number shown above as an asterisk varies by country.

DFX-8000 DIP-switch settings

	ON	OFF
1-1	Condensed printing	Noncondensed printing
1-2	Slashed zero (Ø)	Normal zero (0)
1-3	ESC/P mode: Graphics char. table; IBM mode: CR = no line feed	ESC/P mode: Italics char. table; IBM mode: CR = line feed
1-4	IBM mode	ESC/P mode
1-5	NLQ printing	Draft printing
Country	U.S.	France
1-6	ON	ON
1-7	ON	OFF
1-8	ON	OFF
Country	Germany	U.K.
1-6	ON	ON
1-7	OFF	OFF
1-8	ON	OFF
Country	Denmark	Sweden
1-6	OFF	OFF
1-7	ON	OFF
1-8	OFF	ON
Country	Italy	Spain
1-6	OFF	OFF
1-7	OFF	OFF
1-8	ON	OFF
	ON	OFF
2-1	ESC/P mode: User-defined char.; IBM mode: FF command at TOF	ESC/P mode: ROM char.; IBM mode: No FF command at TOF
2-2	Normal draft printing	High-speed draft printing
2-3	7-bit data length	8-bit data length
2-4	CR command produces a line feed	CR command does not produce a line feed
Interface	Serial (none)	Serial (even)
2-5	ON	ON
2-6	ON	OFF
Interface	Serial (odd)	Parallel
2-5	OFF	OFF
2-6	ON	OFF
Baud	300	1,200
2-7	ON	ON
2-8	ON	OFF
Interface	4,800	9,600
2-7	OFF	OFF
2-8	ON	OFF
	ON	OFF
3-1	No buffer	3-KB buffer
3-2	12-inch page length	11-inch page length
3-3	1-inch skip-over-perforation	No skip-over-perforation
3-4	Paper memory 2	Paper memory 1
3-5	Overlapping multipart forms	Non-overlapping multipart forms
3-6	Multipart forms with labels	Multipart forms with no labels
3-7	Skip-over-binding	No skip-over-binding
3-8	XON/XOFF serial protocol	DTR serial protocol

Built-in features

Print method	9-pin impact		
Speed	NLQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	250 cps @ 10 cpi	300 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Labels, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Not available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8342 (Single-bin)
Tractor	#8307 (Pull)
Roll-paper holder	#8310
Interfaces	#8131, #8132(W), #8133, #8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M)
Color kits	#8391, #8391P
Scanner kit	#8392
Ribbons	#8763 (Fabric), #8764 (Color)

EX-800 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			
Interface	Serial (none)	Serial (even)	Serial (odd)	Parallel				
2-5	ON	ON	OFF	OFF				
2-6	ON	OFF	ON	OFF				
Baud	300	1,200	4,800	9,600				
2-7	ON	ON	OFF	OFF				
2-8	ON	OFF	ON	OFF				

Built-in features

Print method	9-pin impact		
Speed	NLQ	50 cps @ 10 cpi	60 cps @ 12 cpi
	Draft	250 cps @ 10 cpi	300 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Not available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeders	#8343 (Single-bin), #8346 (Double-bin)
Tractor	#8308 (Pull)
Interfaces	#8131, #8132(W), #8133, #8143, #8145, #8148, #8149, 8149(M), #8161, #8165, #8172, #8172(M)
Color kits	#8391, #8391P
Scanner kit	#8392
Ribbons	#8763 (Fabric), #8764 (Color)

EX-1000 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			
Interface	Serial (none)		Serial (even)		Serial (odd)		Parallel	
2-5	ON		ON		OFF		OFF	
2-6	ON		OFF		ON		OFF	
Baud	300		1,200		4,800		9,600	
2-7	ON		ON		OFF		OFF	
2-8	ON		OFF		ON		OFF	

Built-in features

Print method	9-pin impact
Speed	Draft 160 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	2KB
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8331 (Single-bin)
Tractor	#8300 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8165, #8172
Ribbon	#8750 (Fabric)

FX-80 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Paper-end sensor off				Paper-end sensor on			
1-4	2-KB buffer				No buffer			
1-5	Emphasized printing				Normal printing			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON				OFF			
2-1	Receive SLCT IN signal				SLCT IN signal ignored			
2-2	Bell available				Bell disabled			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR does not cause line feed			

Built-in features

Print method	9-pin impact
Speed	Draft 160 cps @ 10 cpi 96 cps @ 12 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	2KB
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8331 (Single-bin)
Tractor	#8300 (Pull)
Roll-paper holder	#8310
Interfaces	#8120, #8131, #8132, #8143, #8145, #8148, #8149, #8161, #8165, #8171, #8172, #8190
Ribbon	#8750 (Fabric)

FX-80+ DIP-switch settings

		ON				OFF				
1-1		Condensed printing				Noncondensed printing				
1-2		Slashed zero (Ø)				Normal zero (0)				
1-3		Paper-end sensor off				Paper-end sensor on				
1-4		2-KB buffer				No buffer				
1-5		Emphasized printing				Normal printing				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
		ON				OFF				
2-1	Receive <u>SLCT IN</u> signal				<u>SLCT IN</u> signal ignored					
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off					
2-3	1-inch skip-over-perforation				No skip-over-perforation					
2-4	CR command produces a line feed				CR command does not produce a line feed					

Built-in features

Print method	9-pin impact
Speed	Draft 160 cps @ 10 cpi 96 cps @ 12 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	8KB
Interface	Parallel
Font (typeface)	Roman
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8331 (Single-bin)
Tractor	#8300 (Pull)
Roll-paper holder	#8310
Interfaces	#8120, #8131, #8132, #8132(W), #8133, #8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M)
Ribbon	#8750 (Fabric)

FX-85 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Paper-end sensor off				Paper-end sensor on			
1-4	ESC/P mode				IBM mode			
1-5	Emphasized printing				Normal printing			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	Receive <u>SLCT IN</u> signal	<u>SLCT IN</u> signal ignored
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8348 (Single-bin)
Tractor	#8307 (Pull)
Interfaces	#8148, #8172
Ribbon	#8755(M) (Fabric)

FX-86e DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	ESC/P mode: Graphics character table IBM mode: CR produces no line feed				ESC/P mode: Italics character table IBM mode: CR produces line feed			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact
Speed	Draft 160 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	2KB
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8334 (Single-bin)
Tractor	#8301 (Pull)
Interfaces	#8145, #8172
Ribbon	#8755 (Fabric)

FX-100 DIP-switch settings

		ON				OFF				
1-1		Condensed printing				Noncondensed printing				
1-2		Slashed zero (Ø)				Normal zero (0)				
1-3		Paper-end sensor off				Paper-end sensor on				
1-4		2-KB buffer				No buffer				
1-5		Emphasized printing				Normal printing				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
		ON				OFF				
2-1		Receive SLCT IN signal				SLCT IN signal ignored				
2-2		Bell available				Bell disabled				
2-3		1-inch skip-over-perforation				No skip-over-perforation				
2-4		CR command produces a line feed				CR command does not produce a line feed				

Built-in features

Print method	9-pin impact
Speed	Draft 160 cps @ 10 cpi 96 cps @ 12 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	2KB
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8333 (Single-bin)
Interfaces	#8120, #8131, #8132, #8143, #8145, #8148, #8149, #8161, #8165, #8171, #8172, #8190
Ribbon	#8755 (Fabric)

FX-100+ DIP-switch settings

	ON					OFF			
1-1	Condensed printing					Noncondensed printing			
1-2	Slashed zero (Ø)					Normal zero (0)			
1-3	Paper-end sensor off					Paper-end sensor on			
1-4	2-KB buffer					No buffer			
1-5	Emphasized printing					Normal printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain	
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF	
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF	
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF	
	ON					OFF			
2-1	Receive <u>SLCT IN</u> signal					<u>SLCT IN</u> signal ignored			
2-2	Cut-sheet feeder mode on					Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation					No skip-over-perforation			
2-4	CR command produces a line feed					CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	32 cps @ 10 cpi	
	Draft	160 cps @ 10 cpi	96 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB		
Interface	Parallel		
Font (typeface)	Roman		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8334 (Single-bin)
Interfaces	#8120, #8131, #8132, #8132(W), #8133, #8143, #8145, #8148, #8149, #8149(M), #8161, #8165, #8172, #8172(M)
Ribbon	#8755 (Fabric)

FX-185 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Paper-end sensor off				Paper-end sensor on			
1-4	ESC/P mode				IBM mode			
1-5	Emphasized printing				Normal printing			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	Receive <u>SLCT IN</u> signal	<u>SLCT IN</u> signal ignored
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	8KB		
Interface	Parallel		
Font (typeface)	Roman		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8334 (Single-bin)
Interfaces	#8148, #8165, #8172
Ribbon	#8755 (Fabric)

FX-286 DIP-switch settings

		ON			OFF			
1-1		Condensed printing				Noncondensed printing		
1-2		Slashed zero (Ø)				Normal zero (0)		
1-3		Paper-end sensor off				Paper-end sensor on		
1-4		ESC/P mode				IBM mode		
1-5		Emphasized printing				Normal printing		
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
		ON			OFF			
2-1	Receive <u>SLCT IN</u> signal			<u>SLCT IN</u> signal ignored				
2-2	Cut-sheet feeder mode on			Cut-sheet feeder mode off				
2-3	1-inch skip-over-perforation			No skip-over-perforation				
2-4	CR command produces a line feed			CR command does not produce a line feed				

Built-in features

Print method	9-pin impact		
Speed	LQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8348 (Single-bin)
Tractor	#8308 (Pull)
Interfaces	#8148, #8165, #8172
Ribbon	#8755(M) (Fabric)

FX-286e DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	ESC/P mode: Graphics character table IBM mode: CR produces no line feed				ESC/P mode: Italics character table IBM mode: CR produces line feed			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8348 (Single-bin)
Interfaces	#8148, #8165, #8172
Ribbon	#8755(M) (Fabric)

FX-800 DIP-switch settings

Switch	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	ESC/P mode: Graphics character table IBM mode: CR produces no line feed				ESC/P mode: Italics character table IBM mode: CR produces line feed			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	45 cps @ 10 cpi	54 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Roll paper		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	#7339 (Single-bin)
Tractor	#7311 (Pull)
Roll-paper holder	#8310
Interfaces	#8133(W), #8143, #8145, #8148, #8149, #8149M, #8165, #8172
Ribbon	#8750 (Fabric)

FX-850 DIP-switch settings

	ON				OFF			
1-1	User-defined characters				ROM characters			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	IBM mode				ESC/P mode			
1-5	No automatic tear-off				Automatic tear-off			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	45 cps @ 10 cpi	54 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
	High-speed draft		290 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	#7339 (Single-bin), #7346 (Double-bin)
Tractor	#7311 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

FX-850 DIP-switch settings

	ON	OFF
1-1	User-defined characters	ROM characters
1-2	Slashed zero (Ø)	Normal zero (0)
1-3	Graphics character table	Italics character table
1-4	IBM mode	ESC/P mode
1-5	No automatic tear-off	Automatic tear-off

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	12-inch page length	11-inch page length
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact
Speed	NLQ 45 cps @ 10 cpi 54 cps @ 12 cpi
	Draft 220 cps @ 10 cpi 264 cps @ 12 cpi
	High-speed draft 290 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif

Options (with model numbers)

Cut-sheet feeders	#7339 (Single-bin), #7346 (Double-bin)
Tractor	#7311 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

FX-850 DIP-switch settings

	ON				OFF			
1-1	User-defined characters				ROM characters			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character tables				Italics character table			
Paper length	11.7 inches	12 inches	8.5 inches	11 inches				
1-4	ON	ON	OFF	OFF				
1-5	ON	OFF	ON	OFF				
Country (1-3 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-3 ON)	PC437	PC850	PC860	PC863	PC865			
1-6	ON	ON	ON	ON	ON			
1-7	ON	ON	OFF	OFF	OFF			
1-8	ON	OFF	ON	ON	OFF			
	ON				OFF			
2-1	IBM mode				ESC/P mode			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	57 cps @ 10 cpi	68 cps @ 12 cpi
	Draft	285 cps @ 10 cpi	342 cps @ 12 cpi
	High-speed draft		380 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Bottom, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	24KB or 0KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	C80637* (Single-bin), C80638* (High-capacity)
Tractor	C80020* (Pull)
Roll-paper holder	#8310
Interfaces	C823051, C823061, C823131, C823081, C823101, C823102, C823131, C823132
Ribbon	#8750 (Fabric)

*The last digit of the option model number shown above as an asterisk varies by country.

FX-870 settings

This printer has no DIP switches; however, the following settings can be made in a special Default-Setting mode.

Setting	Options
Character table	PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC861*, PC863, PC864*, PC865, PC866*, PC869*, U.S.S.R. GOST*, BRASCII**, Abicomp**
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Automatic tear-off	On or Off
Printer mode	EPSON ESC/P or IBM
Shape of zero	Normal zero (0) or Slashed zero (Ø)
Buffer	Enable or Disable
Draft print speed	Normal or High
Auto carriage return	Valid or Invalid †
Auto line feed	On or Depends on interface
Character pitch	10 or 12 cpi

*These tables are only available on the European version.

**These tables are only available on the American version.

†This setting is available only in IBM mode.

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractors	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8348 (Single-bin)
Interfaces	#8148, #8165, #8172
Ribbon	#8755(M) (Fabric)

FX-1000 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	ESC/P mode: Graphics character table IBM mode: CR produces no line feed				ESC/P mode: Italics character table IBM mode: CR produces line feed			
1-4	IBM mode				ESC/P mode			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	45 cps @ 10 cpi	54 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#7340 (Single-bin)
Tractor	#7312 (Pull)
Interfaces	#8133(W), #8143, #8145, #8148, #8149, #8149M, #8165, #8172
Ribbon	#8755 (Fabric)

FX-1050 DIP-switch settings

	ON				OFF			
1-1	User-defined characters				ROM characters			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	IBM mode				ESC/P mode			
1-5	No automatic tear-off				Automatic tear-off			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	45 cps @ 10 cpi	54 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
	High-speed draft		290 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	8KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	#7340 (Single-bin), #7348 (Double-bin)
Tractor	#7312 (Pull)
Interfaces	#8143, #8148, #8165
Ribbon	#8755 (Fabric)

FX-1050 DIP-switch settings

	ON	OFF						
1-1	User-defined characters	ROM characters						
1-2	Slashed zero (Ø)	Normal zero (0)						
1-3	Graphics character table	Italics character table						
1-4	IBM mode	ESC/P mode						
1-5	No automatic tear-off	Automatic tear-off						
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON	OFF						
2-1	12-inch page length	11-inch page length						
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off						
2-3	1-inch skip-over-perforation	No skip-over-perforation						
2-4	CR command produces a line feed	CR command does not produce a line feed						

Built-in features

Print method	9-pin impact
Speed	NLQ 45 cps @ 10 cpi Draft 220 cps @ 10 cpi High-speed draft 290 cps @ 10 cpi
Print width	13.6 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 3 copies
Paper paths	Rear, Top
Tractor	Push
Paper parking	Available
Buffer size	8KB
Interface	Parallel
Fonts (typefaces)	Roman, Sans Serif

Options (with model numbers)

Cut-sheet feeders	#7340 (Single-bin), #7348 (Double-bin)
Tractor	#7312 (Pull)
Interfaces	#8143, #8148, #8165
Ribbon	#8755 (Fabric)

FX-1050 DIP-switch settings

	ON				OFF			
1-1	User-defined characters				ROM characters			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character tables				Italics character table			
Paper length	11.7 inches	12 inches	8.5 inches	11 inches				
1-4	ON	ON	OFF	OFF				
1-5	ON	OFF	ON	OFF				
Country 1-3 OFF	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table 1-3 ON	PC437	PC850	PC860	PC863	PC865			
1-6	ON	ON	ON	ON	ON			
1-7	ON	ON	OFF	OFF	OFF			
1-8	ON	OFF	ON	ON	ON			
	ON				OFF			
2-1	IBM mode				ESC/P mode			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	57 cps @ 10 cpi	68 cps @ 12 cpi
	Draft	285 cps @ 10 cpi	342 cps @ 12 cpi
	High-speed draft		380 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 3 copies		
Paper paths	Rear, Bottom, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	24KB or 0KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeders	C80639* (Single-bin), C80640* (High-capacity)
Tractor	C80021* (Pull)
Front sheet guide	C814011
Interfaces	C823051, C823061, C823071, C823081, C823101, C823102, C823131, C823132
Ribbon	8755 (Fabric)

*The last digit of the option model number shown above as an asterisk varies by country.

FX-1170 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC861*, PC863, PC864*, PC865, PC866*, PC869*, U.S.S.R. GOST*, BRASCII**, Abicomp**
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Automatic tear-off	On or Off
Printer mode	EPSON ESC/P or IBM
Shape of zero	Normal zero (0) or Slashed zero (Ø)
Buffer	Enable or Disable
Draft print speed	Normal or High
Auto carriage return	Valid or Invalid †
Auto line feed	On or Depends on interface
Character pitch	10 or 12 cpi

* Availability varies by country.

** These tables are only available on the American version.

† This setting is available only in IBM mode.

Built-in features

Print method	18-pin impact		
Speed	NLQ	66 cps @ 10 cpi	79 cps @ 12 cpi
	Draft	330 cps @ 10 cpi	396 cps @ 12 cpi
	High-speed draft		440 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Cards, Roll paper		
Multipart forms	Original plus 5 copies		
Paper paths	Rear, Bottom, Front		
Tractor	Push, Pull		
Paper parking	Available		
Buffer size	64KB or 0KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Bar codes	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET		
Nonprintable area	4.2 mm at the top and bottom of single sheets		

Options (with model numbers)

Cut-sheet feeders	C80673* (High-capacity), C80674* (Second-bin)
Pull tractor unit	C80032*
Roll paper holder	#8310
Interfaces	C82305*, C82306*, C82307*, C82308*, C82310*, C82311*, C82312*, C82313*, C82314*, C82315*, C82331*
Ribbon	S015085 (Cartridge), S010032 (Pack)

*The last digit of the option model number shown above as an asterisk varies by country.

FX-2170 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Page length for front tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Page length for rear tractor	3, 3.5, 4, 5.5, 6, 7, 8, 8.5, 11, 70/6, 12, 14, 17, or Others inches
Skip-over-perforation	On or Off
Auto tear off	On or Off
Auto line feed	On or Off †
Print direction	Bi-d or Uni-d
I/F mode	Auto, Parallel, or Option
Auto I/F wait time	10 or 30 sec.
Software	ESC/P or IBM 2381 Plus
Character table	Italic, PC437, PC437 Greek*, PC774*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC865, PC866*, PC866 LAT*, PC869*, BRASCI, Abicomp, Roman 8, ISO Latin 1, ISO 8859-2*, MAZOWIA*, Code MJK*, ISO 8859-7*, ISO Latin 1T*, Bulgaria*, Estonia*
International character set	U.S.A., France, Germany, U.K., Denmark 1, Sweden, Italy, Spain 1
0 slash	0 or Ø
High speed draft	On or Off
Input buffer	On or Off
Buzzer	On or Off
Auto CR	On or Off †
IBM character table	Table 1 or Table 2 †

* Availability varies by country.

† This setting is available only in IBM mode.

Built-in features

Print method	9-element ink jet
Print width	8 inches
Paper types	Single sheets, Roll paper
Paper paths	Top
Paper parking	Not available
Buffer size	One line
Interface	Parallel
Font (typeface)	Roman
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Roll-paper holder	N/A
Ink cartridge	N/A

HS-80 DIP-switch settings

		ON				OFF			
1-1		CR command produces a line feed				CR command does not produce a line feed			
1-2		Cut-sheet feeder mode on				Cut-sheet feeder mode off			
1-3		NLQ character printing				Draft character printing			
Country		U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-4		ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-5		ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-6		ON	OFF	ON	OFF	ON	OFF	ON	OFF

Built-in features

Print method	9-element ink jet		
Speed	NLQ	45 cps @ 10 cpi	54 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets		
Paper paths	Rear, Top		
Paper parking	Not available		
Buffer size	8KB		
Interfaces	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8347 (Single-bin)
Tractor	#8305 (Pull)
Interfaces	#8131, #8132(W), #8133, #8143, #8145, #8148, #8149, #8149, #8161, #8165, #8172, #8172(M)
Ink cartridge	#8765

IX-800 DIP-switch settings

ON									OFF									
1-1	Condensed printing									Noncondensed printing								
1-2	Slashed zero (Ø)									Normal zero (0)								
1-3	Graphics character table									Italics character table								
1-4	IBM mode									ESC/P mode								
1-5	NLQ printing									Draft printing								
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain										
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF										
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF										
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF										
2-1	12-inch page length									11-inch page length								
2-2	Cut-sheet feeder mode on									Cut-sheet feeder mode off								
2-3	1-inch skip-over-perforation									No skip-over-perforation								
2-4	CR command produces a line feed									CR command does not produce a line feed								
Interface	Serial (none)				Serial (even)				Serial (odd)				Parallel					
2-5	ON				ON				OFF				OFF					
2-6	ON				OFF				ON				OFF					
Baud	300				1,200				4,800				9,600					
2-7	ON				ON				OFF				OFF					

Built-in features

Print method	9-pin impact
Speed	Draft 160 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	2KB
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8331 (Single-bin)
Tractor	#8300 (Pull)
Roll-paper holder	#8310
Interfaces	#8148, #8165, #8172
Ribbons	N/A

JX-80 DIP-switch settings

	ON					OFF			
1-1	Condensed printing					Noncondensed printing			
1-2	Slashed zero (Ø)					Normal zero (0)			
1-3	Paper-end sensor off					Paper-end sensor on			
1-4	2-KB buffer					No buffer			
1-5	Emphasized printing					Normal printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain	
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF	
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF	
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF	
	ON					OFF			
2-1	Receive SLCT IN signal					SLCT IN signal ignored			
2-2	Bell available					Bell disabled			
2-3	1-inch skip-over-perforation					No skip-over-perforation			
2-4	CR command produces a line feed					CR command does not produce a line feed			

Built-in features

Print method	9-pin impact
Speed	NLQ 16 cps @ 10 cpi Draft 100 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 1 copy
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	1KB
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8338 (Single-bin)
Tractor	#8304 (Pull)
Interfaces	#8148, #8165, #8172
Ribbon	#8750 (Fabric)

LX-80 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	NLQ printing				Draft printing			
1-3	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
1-4	Paper-end sensor off				Paper-end sensor on			
1-5	12-inch page length				11-inch page length			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	Slashed zero (Ø)				Normal zero (0)			
2-2	Receive <u>SLCT IN</u> signal				<u>SLCT IN</u> signal ignored			
2-3	CR command produces a line feed				CR command does not produce a line feed			
2-4	Bell disabled				Bell enabled			

Built-in features

Print method	9-pin impact
Speed	NLQ 22 cps @ 10 cpi Draft 120 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	(original plus 1 copies)
Paper paths	Rear, Top
Paper parking	Not available
Buffer size	N/A
Interface	Parallel
Font (typeface)	Roman
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet feeder	#8338 (Single-bin)
Tractor	#8304 (Pull)
Interfaces	#8148, #8165, #8172
Ribbon	#8750 (Fabric)

LX-86 DIP-switch settings

		ON				OFF			
1-1		Condensed printing				Noncondensed printing			
1-2		Graphics character table				Italic character table			
1-3		Cut-sheet feeder mode on				Cut-sheet feeder mode off			
1-4		Paper-end sensor off				Paper-end sensor on			
1-5		12-inch page length				11-inch page length			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain	
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF	OFF
		ON				OFF			
2-1		Slashed zero (Ø)				Normal zero (0)			
2-2		Receive <u>SLCT IN</u> signal				<u>SLCT IN</u> signal ignored			
2-3		CR command produces a line feed				CR command does not produce a line feed			
2-4		Bell disabled				Bell enabled			

Built-in features

Print method	9-pin impact		
Speed	NLQ	40 cps @ 10 cpi	48 cps @ 12 cpi
	Draft	200 cps @ 10 cpi	240 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Front		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Ribbon	S015047 (Fabric)
--------	------------------

LX-100 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Character table	PC437, PC437 Greek*, PC850, PC851*, PC852*, PC853*, PC855*, PC857*, PC860, PC863, PC864*, PC865, PC866*, PC869*, U.S.S.R. GOST*
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Tear-off position	On or Above tear-off edge
Top-of-form position	-3, -2, -1, ±0, 1, 2, 3
Shape of zero	Normal zero (0) or Slashed zero (Ø)
Back feed	Enable or Disable
Auto line feed	On or Off
Character pitch	10 or 12 cpi

* Availability varies by country.

Built-in features

Print method	9-pin impact		
Speed	NLQ	44 cps @ 10 cpi	53 cps @ 12 cpi
	Draft	220 cps @ 10 cpi	264 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear		
Tractor	Detachable push and pull		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel, Serial		
Fonts (typefaces)	Roman, Sans Serif, Draft, Draft Condensed		
Nonprintable area	5.3 mm at the top of single sheets		

Options (with model numbers)

Color Upgrade Kit	C83208*
Cut-sheet feeder	C80637*
Pull tractor	C80030*
Roll-paper holder	#8310
Ribbons	#8750 (Black), S015073 (Color)

*The last digit of the option model number shown above as an asterisk varies by country.

LX-300 default-setting mode

This printer has no DIP switches; however, the following settings can be made in a special default-setting mode.

Setting	Options
Page length	11, 12, 8.5, 70/6 (A4) inches
Character table	Italic, PC437, PC437 Greek*, PC850, PC852*, PC853*, PC855*, PC857*, PC860, PC861, PC863, PC865, PC866*, PC869*, ISO Latin 1T*, ISO 8859-7, Code MJK*, Mazovia*, Bulgaria*, BRASCI, Abicomp
Page length (for continuous paper)	11, 12, 8.5, or 70/6 (A4) inches
Skip-over-perforation	On or Off
Auto tear off	On or Off
Top-of-form position	-3, -2, -1, 0, +1, +2, +3
Shape of zero	Normal zero (0) or slashed zero (Ø)
Auto line feed	On or Off
Character pitch	10 or 12 cpi
Tractor	Single or Double
Interface	Auto (10 sec. wait), Auto (30 sec. wait), Parallel, Serial
Serial I/F bit rate	300, 600, 1200, 2400, 4800, 9600, 19200 bps
Serial I/F parity bit	None, Odd, or Even
Serial I/F data length	7 bit or 8 bit
Serial I/F ETX/ACK	Disable or Enable

* Availability varies by country.

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#7341 (Single-bin)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

LX-400 DIP-switch settings

		ON				OFF				
1-1		Condensed printing				Noncondensed printing				
1-2		Slashed zero (Ø)				Normal zero (0)				
1-3		Graphics character table				Italics character table				
1-4		Paper-end sensor off				Paper-end sensor on				
1-5		NLQ printing				Draft printing				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
		ON				OFF				
2-1		12-inch page length				11-inch page length				
2-2		Cut-sheet feeder mode on				Cut-sheet feeder mode off				
2-3		1-inch skip-over-perforation				No skip-over-perforation				
2-4		CR command produces a line feed				CR command does not produce a line feed				

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

LX-400 DIP-switch settings

	ON				OFF							
1-1	User-defined characters				ROM characters							
1-2	Slashed zero (Ø)				Normal zero (0)							
1-3	Graphics character tables				Italics character table							
Paper length	11.7 inches		12 inches		8.5 inches		11 inches					
1-4	ON		ON		OFF		OFF					
1-5	ON		OFF		ON		OFF					
Country (1-3 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain				
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF				
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF				
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF				
Character table (1-3 ON)	PC437		PC850		PC860		PC863					
1-6	ON		ON		ON		ON					
1-7	ON		ON		OFF		OFF					
1-8	ON		OFF		ON		OFF					
	ON				OFF							
2-1	NLQ printing				Draft printing							
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off							
2-3	1-inch skip-over-perforation				No skip-over-perforation							
2-4	CR command produces a line feed				CR command does not produce a line feed							

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Pull		
Paper parking	Not available		
Buffer size	3KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		
Nonprintable area	22.0 mm at the top of single sheets		

Options (with model numbers)

Cut-sheet feeder	#8349 (Single-bin)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

LX-800 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	Paper-end sensor off				Paper-end sensor on			
1-5	NLQ printing				Draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Font (typeface)	Roman		

Options (with model numbers)

Cut-sheet feeder	C806121 (Single-bin)
Tractor	C800061 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

LX-810 DIP-switch settings

	ON	OFF
1-1	12 cpi	10 cpi
1-2	Slashed zero (Ø)	Normal zero (0)
1-3	Graphics character table	Italics character table
1-4	Automatic tear-off	No automatic tear-off
1-5	Normal draft printing	High-speed draft printing

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	12-inch page length	11-inch page length
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact
Speed	NLQ 25 cps @ 10 cpi 30 cps @ 12 cpi Draft 150 cps @ 10 cpi 180 cps @ 12 cpi High-speed draft 200 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top Push
Tractor	Available
Paper parking	4KB
Buffer size	Parallel
Interface	Roman, Sans Serif
Fonts (typefaces)	

Options (with model numbers)

Cut-sheet feeder	C806121 (Single-bin)
Tractor	C800061 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

LX-810 DIP-switch settings

	ON				OFF			
1-1	12 cpi				10 cpi			
1-2	Slashed zero (Ø)				Normal zero (0)			
Paper length	11.7 inches	12 inches	8.5 inches	11 inches				
1-3	ON	ON	OFF	OFF				
1-4	ON	OFF	ON	OFF				
1-5	Graphics character tables				Italics character table			
Country (1-5 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-5 ON)	PC437	PC850	PC860	PC863	PC865			
1-6	ON	ON	ON	ON	ON			
1-7	ON	ON	OFF	OFF	OFF			
1-8	ON	OFF	ON	OFF	ON			
2-1	Automatic tear-off				No automatic tear-off			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)
Tractor	C800062 (Pull)
Roll-paper holder	#8310
Interfaces	#8143, #8148, #8165
Ribbon	#8750 (Fabric)

LX-850 DIP-switch settings

	ON	OFF
1-1	12 cpi	10 cpi
1-2	Slashed zero (Ø)	Normal zero (0)
1-3	Graphics character table	Italics character table
1-4	Automatic tear-off	No automatic tear-off
1-5	Normal draft printing	High-speed draft printing

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON	OFF
2-1	12-inch page length	11-inch page length
2-2	Cut-sheet feeder mode on	Cut-sheet feeder mode off
2-3	1-inch skip-over-perforation	No skip-over-perforation
2-4	CR command produces a line feed	CR command does not produce a line feed

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	8 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels, Roll paper		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Fonts (typefaces)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806122 (Single-bin)		
Tractor	C800062 (Pull)		
Roll-paper holder	#8310		
Interfaces	#8143, #8148, #8165		
Ribbon	#8750 (Fabric)		

LX-850 DIP-switch settings

1-1	ON			OFF							
1-2	12 cpi			10 cpi							
Paper length	Slashed zero (Ø)			Normal zero (0)							
1-3	ON			OFF			OFF				
1-4	ON			ON			OFF				
1-5	Graphics character tables				Italics character table						
Country (1-5 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain			
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF			
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF			
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF			
Character table (1-5 ON)	PC437	PC850	PC860	PC863	PC865						
1-6	ON	ON	ON	ON	ON	OFF					
1-7	ON	ON	OFF	OFF	OFF	ON					
1-8	ON	OFF	ON	ON	OFF	ON					
2-1	ON			OFF							
2-2	Automatic tear-off			No automatic tear-off							
2-3	Cut-sheet feeder mode on			Cut-sheet feeder mode off							
2-4	1-inch skip-over-perforation			No skip-over-perforation							
	CR command produces a line feed			CR command does not produce a line feed							

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Font (typeface)	Roman		

Options (with model numbers)

Cut-sheet feeder	C806242 (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165
Ribbon	#8755 (Fabric)

LX-1050 DIP-switch settings

	ON				OFF			
1-1	12 cpi				10 cpi			
1-2	Slashed zero (Ø)				Normal zero (0)			
1-3	Graphics character table				Italics character table			
1-4	Automatic tear-off				No automatic tear-off			
1-5	Normal draft printing				High-speed draft printing			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	12-inch page length				11-inch page length			
2-2	Cut-sheet feeder mode on				Cut-sheet feeder mode off			
2-3	1-inch skip-over-perforation				No skip-over-perforation			
2-4	CR command produces a line feed				CR command does not produce a line feed			

Built-in features

Print method	9-pin impact		
Speed	NLQ	25 cps @ 10 cpi	30 cps @ 12 cpi
	Draft	150 cps @ 10 cpi	180 cps @ 12 cpi
	High-speed draft		200 cps @ 10 cpi
Print width	13.6 inches		
Paper types	Continuous, Single sheets, Envelopes, Labels		
Multipart forms	Original plus 2 copies		
Paper paths	Rear, Top		
Tractor	Push		
Paper parking	Available		
Buffer size	4KB		
Interface	Parallel		
Font (typeface)	Roman, Sans Serif		

Options (with model numbers)

Cut-sheet feeder	C806242 (Single-bin)
Tractor	C800142 (Pull)
Interfaces	#8143, #8148, #8165
Ribbon	#8755 (Fabric)

LX-1050 DIP-switch settings

	ON			OFF		
1-1		12 cpi			10 cpi	
1-2		Slashed zero (Ø)			Normal zero (0)	
Paper length	11.7 inches		12 inches	8.5 inches		11 inches
1-3	ON		ON	OFF		OFF
1-4	ON		OFF	ON		OFF
1-5	Graphics character table			Italics character table		
Country (1-5 OFF)	U.S.	France	Germany	U.K.	Denmark	Sweden
1-6	ON	ON	ON	ON	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	OFF
1-8	ON	OFF	ON	OFF	ON	ON
Character table (1-5 ON)	PC437	PC850	PC860	PC863	PC865	
1-6	ON	ON	ON	ON	OFF	
1-7	ON	ON	OFF	OFF	ON	
1-8	ON	OFF	ON	OFF	ON	
	ON			OFF		
2-1	Automatic tear-off			No automatic tear-off		
2-2	Cut-sheet feeder mode on			Cut-sheet feeder mode off		
2-3	1-inch skip-over-perforation			No skip-over-perforation		
2-4	CR command produces a line feed			CR command does not produce a line feed		

Built-in features

Print method	9-pin impact	
Speed	NLQ 40 cps @ 10 cpi 48 cps @ 12 cpi	
Print width	Draft 200 cps @ 10 cpi 240 cps @ 12 cpi	
Paper types	13.6 inches	
Multipart forms	Continuous, Single sheets, Envelopes, Labels	
Paper paths	Original plus 2 copies	
Tractor	Rear, Top	
Paper parking	Push	
Buffer size	Available	
Interface	4KB	
Font (typeface)	Parallel	
	Roman, Sans Serif	

Options (with model numbers)

Cut-sheet feeder	C80624* (Single-bin)
Tractor	C80014* (Pull)
Interfaces	#8143, #8148, #8165
Ribbon	#8755 (Fabric)

*The last digit of the option model numbers shown above as an asterisk varies by country.

LX-1050+ DIP-switch settings

	ON			OFF				
1-1	12 cpi			10 cpi				
1-2	Slashed zero (Ø)			Normal zero (0)				
Page length	11.7 inches	12 inches	8.5 inches	11 inches				
1-3	ON	ON	OFF	OFF	OFF			
1-4	ON	OFF	ON	ON	OFF			
	ON			OFF				
1-5	Graphics character table			Italics character table				
Country (1-5 OFF)	U.S.	France	Germany	U.K.	Denmark I	Sweden	Italy	Spain I
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
Character table (1-5 ON)	PC437	PC850*	PC860*	PC863*	PC865*			
1-6	ON	ON	ON	ON	OFF			
1-7	ON	ON	OFF	OFF	ON			
1-8	ON	OFF	ON	ON	OFF			

*These character tables are available only on the European version.

	ON			OFF		
2-1	Automatic tear-off			No automatic tear-off		
2-2	Cut-sheet feeder mode on			Cut-sheet feeder mode off		
2-3	1-inch skip-over-perforation			No skip-over-perforation		
2-4 †	Auto line feed			No auto line feed		

† This setting is available only in IBM mode.

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper type	Continuous
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Available
Buffer size	N/A
Interface	Parallel

Options (with model numbers)

Ribbon #8750 (Fabric)

MX-80 DIP-switch settings

	ON	OFF
1-1	Not used	Not used
1-2	CR command produces a line feed	CR command does not produce a line feed
1-3	Full buffer produces a CR command	Full buffer produces a line feed
1-4	CAN command not available	CAN command available
1-5	DEL command not available	DEL command available
1-6	Bell enabled	Bell disabled
1-7	Katakana character table	Graphics character table
1-8	Receive SLCT IN signal	SLCT IN signal ignored

Country	U.S.	France	Germany	U.K.
2-1	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF

	ON	OFF
2-3 †	Automatic line feed	No automatic line feed
2-4	Code table A	Code table B

† This setting is available only in IBM mode.

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Ribbon #8750 (Fabric)

MX-80 F/T DIP-switch settings

	ON	OFF
1-1	Not used	Not used
1-2	CR command produces a line feed	CR command does not produce a line feed
1-3	Full buffer produces a CR command	Full buffer produces a line feed
1-4	CAN command not available	CAN command available
1-5	DEL command not available	DEL command available
1-6	Bell enabled	Bell disabled
1-7	Katakana character table	Graphics character table
1-8	Receive <u>SLCT IN</u> signal	<u>SLCT IN</u> signal ignored

Country	U.S.	France	Germany	U.K.
2-1	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF

	ON	OFF
2-3 †	Automatic line feed	No automatic line feed
2-4	Code table A	Code table B

† This setting is available only in IBM mode.

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Roll paper
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel

Options (with model numbers)

Roll-paper holder	N/A
Ribbon	#8750 (Fabric)

MX-80 Type II DIP-switch settings

	ON	OFF						
1-1	1/8-inch line spacing	1/6-inch line spacing						
1-2	12-inch page length	11-inch page length						
Print type	Emphasized	Not used						
1-3	ON	ON						
1-4	ON	OFF						
1-5	ON	OFF						
1-6	Not used	Not used						
1-7	Paper-end sensor on	Paper-end sensor off						
1-8	Receive SLCT IN signal	SLCT IN signal ignored						
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-7	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-1	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF	ON	OFF	ON	OFF
2-3	ON	CR command produces line feed			OFF	CR command does not produce a line feed		
2-4		1-inch skip-over-perforation				No skip-over-perforation		

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper path	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Roll-paper holder	N/A
Ribbon	#8750 (Fabric)

MX-80 F/T FType II DIP-switch settings

		ON		OFF				
1-1		1/8-inch line spacing		1/6-inch line spacing				
1-2		12-inch page length		11-inch page length				
Print type	Emphasized	Not used	Condensed	Normal				
1-3	ON	ON	OFF	OFF				
1-4	ON	OFF	ON	OFF				
		ON		OFF				
1-5		Not used		Not used				
1-6		Paper-end sensor on		Paper-end sensor off				
1-8		Receive SLCT IN signal		SLCT IN signal ignored				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-7	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-1	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF	ON	OFF	ON	OFF
		ON		OFF				
2-3		CR command produces line feed		CR command does not produce a line feed				
2-4		1-inch skip-over-perforation		No skip-over-perforation				

MX-80 Type III

*Year introduced: 1982
Market: America, Europe, Pacific*

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Roll paper
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel

Options (with model numbers)

Roll-paper holder	N/A
Interface	#8143
Ribbon	#8750 (Fabric)

MX-80 Type III DIP-switch settings

		ON		OFF				
1-1		1/8-inch line spacing		1/6-inch line spacing				
1-2		12-inch page length		11-inch page length				
Print type	Emphasized	Not used	Condensed	Normal				
1-3	ON	ON	OFF	OFF				
1-4	ON	OFF	ON	OFF				
		ON		OFF				
1-5		Not used		Not used				
1-6		Paper-end sensor on		Paper-end sensor off				
1-8		Receive SLCT IN signal		SLCT IN signal ignored				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-7	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-1	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF	ON	OFF	ON	OFF
		ON		OFF				
2-3		CR command produces line feed		CR command does not produce a line feed				
2-4		1-inch skip-over-perforation		No skip-over-perforation				

MX-80 F/T Type III

Year introduced: 1982
Market: America, Europe, Pacific

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Roll-paper holder	N/A
Interface	#8143
Ribbon	#8750 (Fabric)

MX-80 F/T Type III DIP-switch settings

	ON			OFF				
1-1	1/8-inch line spacing			1/6-inch line spacing				
1-2	12-inch page length			11-inch page length				
Print type	Emphasized	Not used	Condensed	Normal				
1-3	ON	ON	OFF	OFF				
1-4	ON	OFF	ON	OFF				
	ON			OFF				
1-5	Not used			Not used				
1-6	Paper-end sensor on			Paper-end sensor off				
1-8	Receive <u>SLCT IN</u> signal			<u>SLCT IN</u> signal ignored				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-7	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-1	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON			OFF				
2-3	CR command produces line feed			CR command does not produce a line feed				
2-4	1-inch skip-over-perforation			No skip-over-perforation				

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel

Options (with model numbers)

Roll-paper holder	N/A
Ribbon	#8750 (Fabric)

MX-82 DIP-switch setting

		ON	OFF	
1-1		1/8-inch line spacing		1/6-inch line spacing
1-2		12-inch page length		11-inch page length
Print type	Emphasized	Not used	Condensed	Normal
1-3	ON	ON	OFF	OFF
1-4	ON	OFF	ON	OFF
		ON	OFF	
1-5		Not used		Not used
1-6		Paper-end sensor on		Paper-end sensor off
1-8	Receive SLCT IN signal		SLCT IN signal ignored	
Country	U.S.	France	Germany	U.K.
1-7	ON	ON	ON	ON
2-1	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF
		ON	OFF	
2-3		CR command produces line feed		CR command does not produce a line feed
2-4		1-inch skip-over-perforation		No skip-over-perforation

MX-82 F/T Type III

Year introduced: 1982

Market: Europe, Pacific

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets, Roll paper
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Roll-paper holder	N/A
Ribbon	#8750 (Fabric)

MX-82 F/T Type III DIP-switch settings

		ON		OFF	
1-1		1/8-inch line spacing		1/6-inch line spacing	
1-2		12-inch page length		11-inch page length	
Print type	Emphasized	Not used	Condensed	Normal	
1-3	ON	ON	OFF	OFF	
1-4	ON	OFF	ON	OFF	
		ON	OFF		
1-5		Not used		Not used	
1-6		Paper-end sensor on		Paper-end sensor off	
1-8	Receive SLCT IN signal			SLCT IN signal ignored	
Country	U.S.	France	Germany	U.K.	Denmark
1-7	ON	ON	ON	ON	OFF
2-1	ON	ON	OFF	OFF	ON
2-2	ON	OFF	ON	OFF	ON
		ON	OFF		
2-3		CR command produces line feed		CR command does not produce a line feed	
2-4		1-inch skip-over-perforation		No skip-over-perforation	

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	13.6 inches
Paper type	Continuous
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line

Options (with model numbers)

Ribbon #8755 (Fabric)

MX-100 DIP-switch settings

	ON		OFF	
1-1	1/8-inch line spacing		1/6-inch line spacing	
1-2	12-inch page length		11-inch page length	
Print type	Emphasized	Not used	Condensed	Normal
1-3	ON	ON	OFF	OFF
1-4	ON	OFF	ON	OFF
	ON		OFF	
1-5	Not used		Not used	
1-6	Paper-end sensor on		Paper-end sensor off	
1-8	Receive <u>SLCT IN</u> signal		<u>SLCT IN</u> signal ignored	
Country	U.S.	France	Germany	U.K.
1-7	ON	ON	ON	ON
2-1	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF
	ON		OFF	
2-3	CR command produces line feed		CR command does not produce a line feed	
2-4	1-inch skip-over-perforation		No skip-over-perforation	

Built-in features

Print method	9-pin impact
Speed	Draft 80 cps @ 10 cpi
Print width	13.6 inches
Paper type	Continuous
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel

Options (with model numbers)

Interface	#8143
Ribbon	#8755 (Fabric)

MX-100 Type III DIP-switch settings

	ON	OFF						
1-1	1/8-inch line spacing	1/6-inch line spacing						
1-2	12-inch page length	11-inch page length						
Print type	Emphasized	Not used						
1-3	ON	ON						
1-4	ON	OFF						
1-5	ON	OFF						
1-6	Not used	Not used						
1-7	Paper-end sensor on	Paper-end sensor off						
1-8	Receive SLCT IN signal	SLCT IN signal ignored						
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-7	ON	ON	ON	ON	OFF	OFF	OFF	OFF
2-1	ON	ON	OFF	OFF	ON	ON	OFF	OFF
2-2	ON	OFF	ON	OFF	ON	OFF	ON	OFF
2-3	ON	CR command produces line feed			OFF	CR command does not produce a line feed		
2-4		1-inch skip-over-perforation				No skip-over-perforation		

Built-in features

Print method	9-element thermal
Speed	Draft 80 cps @ 10 cpi
Print width	8 inches
Paper types	Single sheets, Roll paper (thermal)
Paper paths	Rear, Top
Paper parking	Available
Buffer size	240 bytes
Interface	Serial (6-pin DIN connector)
Font (typeface)	Roman
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Roll-paper holder	N/A
Ribbons	#8760 (Film, thermal)

P-80 DIP-switch settings

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-1	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-2	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-3	ON	OFF	ON	OFF	ON	OFF	ON	OFF
ON						OFF		
1-4	CR command produces a line feed						CR command does not produce a line feed	
2-1	7-bit data length						8-bit data length	
2-2	Parity checked						No parity check	
2-3	Even parity						Odd parity	
2-4	1 stop bit						2 stop bits	
bps	75	1,800	200	300	134.5	4,800	600	2,400
2-5	ON	ON	ON	ON	ON	ON	OFF	OFF
2-6	ON	ON	ON	ON	OFF	OFF	ON	ON
2-7	ON	ON	OFF	OFF	ON	ON	OFF	ON
2-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

Built-in features

Print method	9-pin impact
Speed	Draft 100 cps @ 10 cpi
Print width	8 inches
Paper type	Continuous
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel

Options (with model numbers)

Roll-paper holder	N/A
Interface	#8143
Ribbon	#8750 (Fabric)

RX-80 DIP-switch settings

		ON				OFF				
1-1		Condensed printing				Noncondensed printing				
1-2		Print codes 128 to 159 as characters				Use codes 128 to 159 as control codes				
1-3		Bell disabled				Bell enabled				
1-4		12-inch page length				11-inch page length				
1-5		Paper-end sensor off				Paper-end sensor on				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
		ON				OFF				
2-1		Slashed zero (Ø)				Normal zero (0)				
2-2		Receive SLCT IN signal				SLCT IN signal ignored				
2-3		CR command produces line feed				CR command does not produce a line feed				
2-4		1-inch skip-over-perforation				No skip-over-perforation				

Built-in features

Print method	9-pin impact
Speed	Draft 100 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Interface	#8143
Ribbon	#8750 (Fabric)

RX-80 F/T DIP-switch settings

		ON				OFF				
1-1		Condensed printing				Noncondensed printing				
1-2		Print codes 128 to 159 as characters				Use codes 128 to 159 as control codes				
1-3		Bell disabled				Bell enabled				
1-4		12-inch page length				11-inch page length				
1-5		Paper-end sensor off				Paper-end sensor on				
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain		
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF		
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF		
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF		
		ON				OFF				
2-1		Slashed zero (Ø)				Normal zero (0)				
2-2		Receive SLCT IN signal				SLCT IN signal ignored				
2-3		CR command produces line feed				CR command does not produce a line feed				
2-4		1-inch skip-over-perforation				No skip-over-perforation				

Built-in features

Print method	9-pin impact
Speed	Draft 100 cps @ 10 cpi
Print width	8 inches
Paper types	Continuous, Single sheets
Multipart forms	Original plus 2 copies
Paper paths	Rear, Top
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel
Nonprintable area	22.0 mm at the top of single sheets

Options (with model numbers)

Cut-sheet-feeder	#8330 (Single-bin)
Interfaces	#8120, #8131, #8132, #8143, #8145, #8146, #8148, #8149, #8161, #8165, #8171, #8172, #8177, #8647
Ribbon	#8750 (Fabric)

RX-80 F/T+ DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Print codes 128 to 159 as characters				Use codes 128 to 159 as control codes			
1-3	Bell disabled				Bell enabled			
1-4	12-inch page length				11-inch page length			
1-5	Paper-end sensor off				Paper-end sensor on			

Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF

	ON				OFF			
2-1	Slashed zero (Ø)				Normal zero (0)			
2-2	Receive SLCT IN signal				SLCT IN signal ignored			
2-3	CR command produces line feed				CR command does not produce a line feed			
2-4	1-inch skip-over-perforation				No skip-over-perforation			

Built-in features

Print method	9-pin impact
Speed	Draft 100 cps @ 10 cpi
Print width	13.6 inches
Paper type	Continuous
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line
Interface	Parallel

Options (with model numbers)

Interface	#8143
Ribbon	#8755 (Fabric)

RX-100 DIP-switch settings

	ON				OFF			
1-1	Condensed printing				Noncondensed printing			
1-2	Print codes 128 to 159 as characters				Use codes 128 to 159 as control codes			
1-3	Bell disabled				Bell enabled			
1-4	12-inch page length				11-inch page length			
1-5	Paper-end sensor off				Paper-end sensor on			
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF
	ON				OFF			
2-1	Slashed zero (Ø)				Normal zero (0)			
2-2	Receive SLCT IN signal				SLCT IN signal ignored			
2-3	CR command produces line feed				CR command does not produce a line feed			
2-4	1-inch skip-over-perforation				No skip-over-perforation			

Built-in features

Print method	9-pin impact
Speed	Draft 100 cps @ 10 cpi
Print width	13.6 inches
Paper type	Continuous
Multipart forms	Original plus 2 copies
Paper path	Rear
Tractor	Pull
Paper parking	Not available
Buffer size	One line

Options (with model numbers)

Interfaces	#8120, #8131, #8132, #8143, #8145, #8146, #8148, #8149, #8461, #8165, #8171, #8172, #8177, #8647
Ribbon	#8755 (Fabric)

RX-100+ DIP-switch settings

		ON				OFF			
1-1		Condensed printing				Noncondensed printing			
1-2		Print codes 128 to 159 as characters				Use codes 128 to 159 as control codes			
1-3		Bell disabled				Bell enabled			
1-4		12-inch page length				11-inch page length			
1-5		Paper-end sensor off				Paper-end sensor on			
<hr/>									
Country	U.S.	France	Germany	U.K.	Denmark	Sweden	Italy	Spain	
1-6	ON	ON	ON	ON	OFF	OFF	OFF	OFF	
1-7	ON	ON	OFF	OFF	ON	ON	OFF	OFF	
1-8	ON	OFF	ON	OFF	ON	OFF	ON	OFF	
<hr/>									
2-1	ON Slashed zero (Ø)				OFF Normal zero (0)				
2-2	Receive SLCT IN signal				SLCT IN signal ignored				
2-3	CR command produces line feed				CR command does not produce a line feed				
2-4	1-inch skip-over-perforation				No skip-over-perforation				