



- Notes:
1. Model 930 uses D1 and D2 rated 25 amp.
 2. Model 940 used D1 and D2 rated 50 amp.
 3. Model 950 may use D1 and D2 rated 50 amp or D1-D4 rated 25 amp.
 4. C1 - 10 mfd 660 VAC
 5. C2, C3- (if used) rated .47 mfd 250 volt (optional component)
 6. TS3- may be used on UL model and must be used on -2 models.
 7. TS4- Thermal one-shot, integral part of transformer, not field serviceable.

REV.	CHANGE	DATE	DWN BY	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES: TOLERANCES X/X=P1/64 .XX=P.01 .XXX=P.005 ↗=POD 30' THIS DRAWING CONTAINS INFOR- MATION PROPRIETARY TO PARALLAX POWER COMPONENTS, LLC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY PRO- HIBITED EXCEPT AS PARALLAX MAY OTHERWISE AGREE IN WRITING.	
A	RELEASED	02/27/02	Martin W. Redd		
			DES.ENG. Martin W. Redd		
			QUALITY		
			MFG.ENG.		
			RELSE		
			TITLE 900 SERIES MODEL 930,940,950		
SIZE		THIRD ANGLE PROJECTION		DWG NO.	
SCALE		None		900 Series Model 930,940,950	
				SHEET Sheet 1 of 1	