



Technical Data Sheet 2.0" 5*7 Dot Matrix Displays


ELM-2001EWA

■ Features :

- Large emitting dot 0.2" diameter.
- Low power/high brightness.
- Pb free

■ Descriptions :

- The ELM-2001 series is a large emitting area(5.0mm diameter)LED sources configured in a 35 dots 5*7 matrix array.
- These devices are made with white dots and gray surface.



■ Applications :

- Instrument panels
- Digital read out display


PART NO.	Chip	
	Material	Emitted Color
ELM-2001EWA	GaAsP/GaP	Orange

Technical Data Sheet

2.0" 5*7 Dot Matrix Displays

ELM-2001EWA

Package Dimensions



Notes: 1. All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.

2. Above specification may be changed without notice.

Supplier will reserve authority on material change for above specification.

**Technical Data Sheet**
2.0" 5*7 Dot Matrix Displays**ELM-2001EWA**

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	V _R	5	V
Forward Current	I _F	30	mA
Operating Temperature	T _{opr}	-40 to +85	°C
Storage Temperature	T _{stg}	-40 to +100	°C
Soldering Temperature	T _{sol}	260 ± 5	°C
Power Dissipation	P _d	100	mW
Peak Forward Current(Duty 1/10 @ 1KHz)	I _{F(Peak)}	160	mA

■ Electronic optical characteristics :

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I _v	2.0	4.5	----	mcd	I _F =10mA
Peak Wavelength	λ _p	----	635	----	nm	I _F =20mA
Dominant Wavelength	λ _d	----	625	----	nm	I _F =20mA
Spectrum Radiation Bandwidth	△λ	----	45	----	nm	I _F =20mA
Forward Voltage	V _F	1.7	2.0	2.4	V	I _F =20mA
Reverse Current	I _R	----	----	10	μA	V _R =5V






Technical Data Sheet 2.0" 5*7 Dot Matrix Displays

ELM-2001EWA

■ Typical Electro-Optical Characteristic Curves:

CHIP Material:GaAsP/GaP
Emitted Color:Hi-Eff Red/Orange



**Technical Data Sheet**
2.0" 5*7 Dot Matrix Displays**ELM-2001EWA****■ Reliability test items and conditions:**

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min § 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min § 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1