


## Miniature Glass Passivated Single-Phase Surface Mount Bridge Rectifiers



Case Style DFS

### FEATURES

- UL recognition, file number E54214
- Ideal for automated placement
- High surge current capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 250 °C
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

General purpose use in ac-to-dc bridge full wave rectification for SMPS, lighting ballaster, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

### PRIMARY CHARACTERISTICS

|             |                |
|-------------|----------------|
| $I_{F(AV)}$ | 1 A            |
| $V_{RRM}$   | 50 V to 1000 V |
| $I_{FSM}$   | 50 A           |
| $I_R$       | 5 $\mu$ A      |
| $V_F$       | 1.1 V          |
| $T_J$ max.  | 150 °C         |

### MECHANICAL DATA

**Case:** DFS

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test

**Polarity:** As marked on body

### MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)

| PARAMETER                                                                        | SYMBOL         | DF005S        | DF01S | DF02S | DF04S | DF06S | DF08S | DF10S | UNIT             |
|----------------------------------------------------------------------------------|----------------|---------------|-------|-------|-------|-------|-------|-------|------------------|
| Device marking code                                                              |                | DF005S        | DF01S | DF02S | DF04S | DF06S | DF08S | DF10S |                  |
| Maximum repetitive peak reverse voltage                                          | $V_{RRM}$      | 50            | 100   | 200   | 400   | 600   | 800   | 1000  | V                |
| Maximum RMS voltage                                                              | $V_{RMS}$      | 35            | 70    | 140   | 280   | 420   | 560   | 700   | V                |
| Maximum DC blocking voltage                                                      | $V_{DC}$       | 50            | 100   | 200   | 400   | 600   | 800   | 1000  | V                |
| Maximum average forward output rectified current at $T_A = 40$ °C <sup>(1)</sup> | $I_{F(AV)}$    | 1.0           |       |       |       |       |       |       | A                |
| Peak forward surge current single half sine-wave superimposed on rated load      | $I_{FSM}$      | 50            |       |       |       |       |       |       | A                |
| Rating for fusing ( $t < 8.3$ ms)                                                | $I^2t$         | 10            |       |       |       |       |       |       | A <sup>2</sup> s |
| Operating junction and storage temperature range                                 | $T_J, T_{STG}$ | - 55 to + 150 |       |       |       |       |       |       | °C               |

#### Note:

(1) Units mounted on P.C.B. with 0.51 x 0.51" (13 x 13 mm) copper pads

| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted) |                                                                           |        |            |       |       |       |       |       |       |               |
|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|--------|------------|-------|-------|-------|-------|-------|-------|---------------|
| PARAMETER                                                                                      | TEST CONDITIONS                                                           | SYMBOL | DF005S     | DF01S | DF02S | DF04S | DF06S | DF08S | DF10S | UNIT          |
| Maximum instantaneous forward voltage drop per diode                                           | 1.0 A                                                                     | $V_F$  | 1.1        |       |       |       |       |       |       | V             |
| Maximum DC reverse current at rated DC blocking voltage per diode                              | $T_A = 25\text{ }^{\circ}\text{C}$<br>$T_A = 125\text{ }^{\circ}\text{C}$ | $I_R$  | 5.0<br>500 |       |       |       |       |       |       | $\mu\text{A}$ |
| Typical junction capacitance per diode <sup>(1)</sup>                                          |                                                                           | $C_J$  | 25         |       |       |       |       |       |       | pF            |

**Note:**

(1) Measured at 1.0 MHz and applied reverse voltage of 4.0 V

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                  |        |       |       |       |       |       |       |      |
|-------------------------------------------------------------------------|------------------|--------|-------|-------|-------|-------|-------|-------|------|
| PARAMETER                                                               | SYMBOL           | DF005S | DF01S | DF02S | DF04S | DF06S | DF08S | DF10S | UNIT |
| Typical thermal resistance <sup>(1)</sup>                               | R <sub>θJA</sub> | 40     |       |       |       |       |       |       | °C/W |
|                                                                         | R <sub>θJL</sub> | 15     |       |       |       |       |       |       |      |

**Note:**

(1) Units mounted on P.C.B. with 0.51 x 0.51" (13 x 13 mm) copper pads

| <b>ORDERING INFORMATION</b> (Example) |                 |                        |               |                                  |
|---------------------------------------|-----------------|------------------------|---------------|----------------------------------|
| PREFERRED P/N                         | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                    |
| DF06S-E3/45                           | 0.399           | 45                     | 50            | Tube                             |
| DF06S-E3/77                           | 0.399           | 77                     | 1500          | 13" diameter paper tape and reel |


**RATINGS AND CHARACTERISTICS CURVES**( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

Figure 1. Derating Curve Output Rectified Current




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Figure 3. Typical Forward Characteristics Per Diode




Figure 5. Typical Junction Capacitance Per Diode




Figure 4. Typical Reverse Leakage Characteristics Per Diode





Figure 6. Typical Transient Thermal Impedance

## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.